




SMA CONNECTORS



✓ Active

↓ **PRODUCT DRAWING**
English

TE CONNECTIVITY (TE)

SMA B/HD JK M/CRMP RG174 GSS

[SAM](#) , [SMA](#)

1-1478959-0

TE Internal Number: 1-1478959-0

[Always EU RoHS/ELV Compliant](#)

Applies To **Coaxial Cable**

Panel Mount **With**

Body Material **Stainless Steel**

Body Plating Material **Gold**

Panel Mount Retention Type **Bulkhead**

Product Drawings

[SMA STRAIGHT BULKHEAD, JACK SOLDER PIN, CRIMP ATTACHMENT
RG188A/U, RG316/U, RG174A/U, URM95, KX3B, 22A](#)

PDF ([TIFF AVAILABLE](#))
English

[SMA STRAIGHT BULKHEAD, JACK SOLDER PIN, CRIMP ATTACHMENT
RG188A/U, RG316/U, RG174A/U, URM95, KX3B, 22A](#)

PDF ([TIFF AVAILABLE](#))
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Applies To	Coaxial Cable
	RF Connector Type	SMA
	Connector Style	Jack
	Cable Type	KX 22A, KX 3B, RG 174A, RG 188A, RG 316, URM 95
	Product Type	Connector - RF
	Shrink Tubing	Without
	Retractable Collar	Without
	Dielectric Material	PTFE
	Sealed	No
	Flats Dimension	8.0 A/F
	Grade	Professional

	Snap-Lock	Without
Body Features	Body Material	Stainless Steel
	Body Plating Material	Gold
	Body Style	Straight
	Ferrule Material	Brass
	Ferrule Plating Material	Gold
Contact Features	Center Contact Plating Material	Gold
	Center Contact Material	Beryllium Copper
	Captivated Contacts	Without
	Center Contact	With
Termination Features	Cable Termination Type	MIL-Crimp
	Crimp Type	Hex
Mechanical Attachment	Panel Mount	With
	Panel Mount Retention Type	Bulkhead
	Safety Wire Holes	Without
	Lockwasher Material	Mild Steel
	Flange and Thread Material	Stainless Steel
	Number of Panel Mounting Holes	1
	Lockwasher Plating Material	Gold
	Polarized	No
	Panel Attachment Style	Rear Mount
Dimensions	Panel Thickness	3.2 mm [.126 in]
	Length	18.7 mm [.736 in]
Packaging Features	Packaging Method	Box
	Packaging Quantity	100
Product Compliance	Statement of Compliance PDF	
	VIEW ALL PRODUCT COMPLIANCE	

