


## Base strip - STB 3/3-G-5,08 - 1751031

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Header, Nominal current: 16 A, Number of positions: 3, Pitch: 5.08 mm, Color: green, Contact surface: Tin, Mounting: Soldering

### Key commercial data

Packing unit	50 pc
Minimum order quantity	50 pc
GTIN	 4 017918 028305
Weight per Piece (excluding packing)	1.82 g
Custom tariff number	85369010
Country of origin	Poland
Note	Made to Order (non-returnable)

### Technical data

#### Dimensions

Pitch	5.08 mm
Pin dimensions	1 x 0,8 mm
Hole diameter	1.3 mm

#### General

Range of articles	STB
Rated voltage (III/3)	250 V
Connection in acc. with standard	EN-VDE
Nominal current $I_N$	16 A
Color	green
Stripping length	8 mm
Number of positions	3

### Classifications

#### eCl@ss

eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27260701
eCl@ss 6.0	27260704
eCl@ss 7.0	27440490

# Base strip - STB 3/3-G-5,08 - 1751031

## Classifications

### eCl@ss

eCl@ss 8.0	27440402
------------	----------

### ETIM

ETIM 3.0	EC001121
ETIM 4.0	EC002498
ETIM 5.0	EC002637

### UNSPSC

UNSPSC 6.01	30211810
UNSPSC 7.0901	39121409
UNSPSC 11	39121409
UNSPSC 12.01	39121409
UNSPSC 13.2	39121409

## Approvals

### Approvals

#### Approvals

CSA / UL Recognized / EAC

#### Ex Approvals

#### Approvals submitted

### Approval details

CSA	
Nominal current IN	10 A
Nominal voltage UN	300 V

UL Recognized	
Nominal current IN	10 A
Nominal voltage UN	300 V

## Base strip - STB 3/3-G-5,08 - 1751031

### Approvals

EAC
-----

---