HellermannTyton

118-00111

118-00111		
Art	ticle Number: 118-00111	
Ou	utside Serrated Cable Tie, 7.9" Long, 50lb Tensile Strength, PA66HS, Black, 1000/pkg	
	RoHS	
Download drawing	spec sheet	
Base Data		
Local Order Number	118-00111	
Туре	T50ROS	
Color	Black (BK)	
Features and Benefits	 Outside servations minimize damage to cables, while still providing high tensile strength and low insertion force. Contour style head design provides additional space in constrained areas. Heat stabilized material provides excellent resistance to high heat exposures. 	
Product Description	HellermannTyton outside serrated cable ties are designed with a smooth inside surface to help minimize indentation or damage to wire and cable insulation, while offering high tensile strength and low insertion force. The contour style head takes up less space than traditional style cable ties making it ideal for space constrained areas. For high volume applications, tensioning tools are available to ensure consistent and safe installation.	
Fixation Method (FF)	None	
Identification Plate Position	none	
Releasable Closure (Yes/No)	No	
Tie Closure	plastic pawl	
Variant	Outside Serrated	
Short Description	Outside Serrated Cable Tie, 7.9" Long, 50lb Tensile Strength, PA66HS, Black, 1000/pkg	

Product Dimensions

Minimum Tensile Strength (imperial)	50.0 lbs
Minimum Tensile Strength (N)	225.0 N
Length L (imperial)	7.9 "
Length L (metric)	200.0 mm
Width W (imperial)	0.18 "
Width W (metric)	4.6 mm
Height H (imperial)	0.05 "
Height H (metric)	1.3 mm
Bundle Diameter min (imperial)	0.06 "
Bundle Diameter min (metric)	1.6 mm
Bundle Diameter max (imperial)	2.0 "
Bundle Diameter max (metric)	50.0 mm

Logistics and Packaging

Quantity perbagPackage Quantity1000

Material	Polyamide 6.6 heat stabilized (PA66HS)
Material Shortcut	PA66HS
Flammability	UL94 V2
Halogenfree	Yes
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
ROHS Conformity	Yes

© HellermannTyton 2014