

All categories

Search term



Your shopping cart

Products

MyHARTING

Downloads / Catalogue order

Repairservice

Han 10B-HMC-KG-LB-M25

[Spotted an error?](#) | [Print page](#) | [Back](#)

Image is for illustration purposes only.
Please refer to product description.

[Features](#)[Material properties](#)[Dimensions and weight](#)[Version](#)[Norms and specifications](#)

Part number:	19 30 210 0756
Description:	Han 10B-HMC-KG-LB-M25
Type sheet:	PDF

[Login to MyHARTING](#)
for pricing and stock checkQuantity: [Shopping cart](#)[Email inquiry](#)

Need assistance?

**Customer service****Your HARTING customer
service representative:****866-278-0306**[CustomerService-USA@HA ...](mailto:CustomerService-USA@HA...)

Catalogue

Industrial Connectors Han® -
Page 531[Browse](#)[Download](#)

Features

Mating cycles:	>= 10,000
Han-Easy Lock®:	Yes
RoHS conformity:	Yes
Size:	10 B
Material, locking lever:	polycarbonate + stainless steel
Lever type:	single locking lever
Type of hood/housing:	Cable to cable housings
Series:	Han® B HMC
Limiting temperature, min.:	-40 °C
Limiting temperature, max.:	125 °C

[Top](#)

Material properties

Colour, locking element:	RAL 7037 (grey)
Surface, hood/housing:	powder-coated
Material, seal:	NBR
Colour, hood/housing:	RAL 7037 (grey)
Material, hood/housing:	aluminium die-cast

[Top](#)

Dimensions and weight

Net Weight:	193 g
--------------------	-------

[Top](#)

Version

Hoods and Housings: Case of operation:	Metal hoods/housings for industrial applications
No. of cable entries:	1
Size:	M25
Cable entry:	top entry
Style:	High construction

[Top](#)

Norms and specifications

Flammability locking lever acc. to UL 94:	V 0
Protection class acc. to UL 50:	NEMA type 4/4X/12
Approval GL:	Yes











Degree of protection acc. to DIN IP65
EN 60 529:

[Top](#)

Downloads

Title	Download
Type sheet	PDF
Type sheet	DXF
Type sheet	CGM
CAD data 3D	STEP
CAD data 3D	JT
Industrial Connectors Han® - Page 531	PDF

Recently viewed - [Delete](#)

 Han 10B-HMC-KG-LB-M25 Show product details	 Han 24B-HMC-asg1-LB-M25 Show product details
 Han E HMC female contact Au AWG 19 Show product details	 Han 10B-HMC-asg1-LB-M20 Show product details
 Han D F crimp contact 2,5 mm² Au/HMC Show product details	 Han E HMC female contact Au AWG 18 Show product details
 Han 16B-HMC-kg-LB-M32 Show product details	 Han 10B-HMC-asg2-LB-M20 Show product details
 Han 24B-HMC-kg-LB-M32 Show product details	 Han E HMC male contact Au AWG 12 Show product details

Recently searched - [Delete](#)

- All categories: [09302100803](#) (1)
- All categories: [19302160252](#) (1)
- All categories: [19302240292](#) (1)
- All categories: [11000009601](#) (1)
- All categories: [19410060301](#) (1)
- All categories: [han_eco](#) (188)
- All categories: [19410012700](#) (1)
- All categories: [yellock](#) (164)



HARTING contact: HARTING Inc. of N.America | Bowes Road1370 | 60123-5538 Elgin | USA
HARTING support: 866-278-0306 | **E-mail address** (For questions regarding products, orders and user accounts)
Website support: | **E-mail address** (For technical problems regarding the website)

