

151-10906

Article Number: 151-10906

Q Mount with Adhesive, 1.6" x 1.6" x 0.26", 4 way entry for Q18 thru Q120 ties, PA66, White, 100/bag



Download drawing



Download spec sheet

## Base Data

**Local Order Number** 151-10906

**Type** QM40A

**Color** Natural (NA)

**Features and Benefits** • 2- or 4-way entry options for the Q Tie, offering flexibility and stability

**Product Description** Q Mounts are designed to work exclusively with the Q Tie cable tie series. This mounting component is available with adhesive or can be secured with screws. The Q Mount allows either a 2- or 4-way entry for the Q Tie, providing a quick and simple insertion into the mount. Once in place, the Q Tie will not slip out, even in vertical mounting applications.

**Fixation Method (FF)** Screw Mounting and Adhesive

**Short Description** Q Mount with Adhesive, 1.6" x 1.6" x 0.26", 4 way entry for Q18 thru Q120 ties, PA66, White, 100/bag

## Product Dimensions

**Length L (imperial)** 1.6 "

**Length L (metric)** 40.0 mm

**Width W (imperial)** 1.6 "

**Width W (metric)** 40.0 mm

**Cable Tie Width Max (imperial)** 0.31 "

**Cable Tie Width max. (metric)** 8.4 mm

**Height H (imperial)** 0.26 "

**Height H (metric)** 5.5 mm

**Mounting Hole Diameter D (imperial)** 0.16 "

**Mounting Hole Diameter D (metric)** 4.1 mm

**Mounting Hole Diameter D min (imperial)** 0.16 "

**Mounting Hole Centers (imperial)** 1.19 "

**Mounting Hole Centers (metric)** 30.0 mm

## Logistics and Packaging

**Quantity per** bag

**Package Quantity** 50

## Material and Specifications

**Material** Polyamide 6.6 (PA66)

**Material Shortcut** PA66

**Adhesive** Synthetic rubber with base of polyethylene foam

**Shortcut Adhesive** Synthetic rubber

**Adhesive Operating Temperature** -40°F to +140°F (-40°C to +60°C)

**Flammability** UL94 V2 (excluding adhesive)

**Halogenfree** Yes

**Operating Temperature** -40°F to +185°F (-40°C to +85°C)

**ROHS Conformity** Yes