



- NOTES:
1. FOR USE WITH BOEING BMS13-65 OK & ADAMS RUSSELL FC48Z CABLE.
 2. FOR CABLING INSTRUCTIONS SEE 3-546-2.
 3. FOR CRIMPING USE DIE KTH-2229.
 4. INTERFACE PER MIL-STD-348, FIG. 313-1.
 5. CENTER CONTACT (1-7530-1MA9) SUPPLIED UNASSEMBLED.
 6. MARK PACKAGE: KINGS 126-74-9 YRWM (DATE CODE)

7. MATERIALS:
- INSULATORS: TEFLON, ASTM-D1710
 GASKET: SIL. RUB, A-A-59588
 C-RING: PHOS. BRONZE, ASTM-B103
 K-GRIP SLEEVE: COM. BRONZE, ASTM-B-135
 OUTER CONTACT } BER. COP., ASTM-B-196
 CONTACT F }
 ALL OTHER METAL PARTS: BRASS, ASTM-B16

8. FINISHES:
- CENTER CONTACTS: .000050 MIN GOLD PER ASTM B488 OVER .000050 MIN NICKEL PER AMS-QQ-N-290(RoHS)
 OUTER CONTACT: .000200 MIN SILVER PER ASTM B700 OVER .000020 MIN COPPER PER ASTM B734(RoHS)
 ALL OTHER METAL PARTS: .000050 MIN NICKEL PLATE PER AMS-QQ-N-290 OVER .000050 MIN COPPER PER ASTM B734(RoHS)
9. ELECTRICAL CHARACTERISTICS:
- NOMINAL IMPEDANCE: 50 OHMS
 VOLTAGE RATING: 500 VRMS
 FREQUENCY RANGE: DC TO 11 GHZ
10. WEIGHT: 58.9 GRAMS (0.130 POUNDS)

126-74-9

REVISIONS	
ISSUE	CHANGES
0	ER 36173 KH 03/16/95
1	CN 38251 C BDH 03/14/01 ER 33785 COL 07/14/11

SALES DRAWING

THIS DRAWING, THE DESIGN AND IDEAS EMBODIED IN THE DEVICE TO WHICH IT RELATES AND THE METHOD OF PRODUCING THE DEVICE, ARE THE PROPERTY OF WINCHESTER ELECTRONICS CORPORATION AND SHALL NOT BE EMPLOYED, COPIED, OR DISCLOSED TO ANYONE, IN ANY MANNER WITHOUT THE CONSENT OF WINCHESTER ELECTRONICS CORPORATION.

SCALE 4:1
 APPROX SURFACE AREA
 WAS: E-18479
 USED ON
 CAGE CODE: 91836
 PLUG, ANGLE, TNC

DRAWN	DATE
MLB	08/09/94
DESIGN	DATE
CT	08/09/94
APPR.	DATE

KINGS
 BY WINCHESTER
 Winchester Electronics
 1000 North
 Wellington, CT 06422
 A
 SIZE
 126-74-9