

**SAI Passive**  
**SAI-4 M 4P M12 UT**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com



M12 distributors are available in various versions. The 4, 6 or 8 M12 slots are in 4 or 5 pole design. The group outlet is designed as a fixed cable version, hood version for connection by the user, or with M23. Special versions are also available. For instance, there are 1-to-1 distributors for use with any connection types, or distributors approved for Ex Zone 1.

**General ordering data**

Type	SAI-4 M 4P M12 UT
Order No.	<a href="#">1705921000</a>
Version	SAI Passive, Sensor-actuator passive distributor, M12, Hood version, Yes
GTIN (EAN)	4032248147892
Qty.	2 pc(s).

**Data sheet**

**SAI Passive  
SAI-4 M 4P M12 UT**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Technical data**

**Dimensions and weights**

Length	102 mm	Net weight	120 g
--------	--------	------------	-------

**General data**

Number of contact sockets	4	Fire behaviour	V-0
Contact tube diameter	M12	No. of poles	4
Storage space	Standard	Plugging cycles	≤ 50
Pollution severity	3	Distributor outlet	Hood version
Insulation resistance	10 <sup>9</sup> Ω	Rated voltage , max.	30 V
Rated voltage , min.	10 V	Test voltage	1 kV
Current per signal	2 A	Total current	10 A
Max. current-carrying capacity per slot	4 A	Housing main material	Pocan
Housing colour	grey, RAL 7032	Screw socket	CuZn, nickel-plated
Hood sealing material	Viton	Contact material	CuZn
Contact surface	Gold-plated	Contact carrier material	PBT (UL 94 V0)
Clamping range, rated connection, max.	1.5 mm <sup>2</sup>	Clamping range, rated connection, min.	0.08 mm <sup>2</sup>
Conductor O.D.	0 - 0mm	Conductor O.D., max.	0 mm
Conductor O.D., min.	0 mm	LED initiator	Yes
LED	Yes	LED colour for indicating operation	green
LED colour for I/O function	yellow		

**Classifications**

ETIM 3.0	EC001856	UNSPSC	30-21-18-01
eClass 6.2	27-06-91-90	eClass 7.1	27-06-91-90

**Approvals**

Approvals



ROHS Conform

