HellermannTyton

170-03120

	Article Number: 170-03120 Fray Resistant Flame Retardant Expandable Braided Sleeving, 1.0" Dia., Black, 250.0 ft/Bulk Reel
Download drawing	nload spec sheet
Dece Defe	
Base Data	
Local Order Num	ber 170-03120

Ecoal of doi flambol	
Туре	BSSCFR100B
Color	Black (BK)
Features and Benefits	 Increased braid density coverage provides higher level of abrasion resistance without losing flexibility. Treated yarns extinguish quickly and reduces potential flame spread to surrounding components. Cuts with ordinary scissors without fraying ends.
Product Description	Treated polyester yams that can be cut with sharp scissors and provides flame retardant properties. Well suited for situations where access to a hot knife is either impractical or impossible. Contains white tracer thread for easy identification.
Short Description	Fray Resistant Flame Retardant Expandable Braided Sleeving, 1.0" Dia., Black, 250.0 ft/Bulk Reel

Product Dimensions

Length L (Imperial)	250.0 ft
Length L (Metric)	76.2 m
Reel Length (imperial)	250.0 ft
Bundle Diameter Min. (Imperial)	0.75 "
Bundle Diameter Min. (Metric)	19.1 mm
Bundle Diameter Max. (Imperial)	1.2 "
Bundle Diameter Max. (Metric)	30.5 mm
Nominal Diameter (Imperial)	1 "
Nominal Diameter (Metric)	25.4 mm

Logistics and Packaging

Quantity Per	reel
Package Quantity	250 ft
Weight (Metric)	1.4 kg
Weight (imperial)	3.1 lbs

Material and Specifications

Material	Polyester (PET)
Material Shortcut	PET
Flammability	UL VW-1 Mil-202
Operating Temperature	-94°F to +257°F (-70°C to +125°C)

ROHS Compliant Yes

UL Recognized (US and Canada) Yes

© HellermannTyton 2015