HellermannTyton

170-03192

	Article Number: 170-03192
	Aluminum Laminated Fiberglass Wrap, 4-FT Stick, 1/2" Dia., AL; GF, Silver, 25/Box
	Rohs
Download spec sheet	Download tech sheet

Base Data

Local Order Number	170-03192
Туре	BSHTTSW12SB
Color	Silver (SR)
Features and Benefits	 A layer of aluminum provides protection from chemicals, scraping, cuts and abrasion. Additional layer also provides insulation barrier for vulnerable wires and cables within high temperature environments. Cuts with ordinary scissors for fast, easy application.
Product Description	Aluminum Laminated Fiberglass Wrap sleeving combines the protection of bonded aluminum and fiberglass into a robust solution that deflects radiant heat away from sensitive wires and cables. Wrap-around design allows for fast and easy installation and maintenance.
Short Description	Aluminum Laminated Fiberglass Wrap, 4-FT Stick, 1/2" Dia., AL; GF, Silver, 25/Box

Product Dimensions

Length L (Imperial)	4.0 ft
Length L (Metric)	1.22 m
Diameter D (imperial)	0.5 "
Diameter D (metric)	12.7 mm
Nominal Diameter (Imperial)	1/2 "
Nominal Diameter (Metric)	12.70 mm
Wall Thickness WT (Imperial)	0.042 "
Wall Thickness WT (Metric)	1.06 mm

Logistics and Packaging

Quantity Per	box
Package Quantity	25
Package Quantity (Metric)	25
Carton Quantity	25

Material and Specifications

Material	Glass fiber with aluminium foil (GF-AL)
Material Shortcut	GF-AL
Flammability	non flammable
Operating Temperature	-76°F to +491°F (-60°C to +255°C)
ROHS Compliant	Yes

© HellermannTyton 2015