


# SPECIFICATION CONTROL DRAWING

CTC-0057

Title	TWO CONDUCTOR THERMOCOUPLE EXTENSION CABLE, SHIELDED, JACKETED	Date	10-11-03	Revision	C
-------	---	------	----------	----------	---

This specification sheet forms a part of the latest issue of Raychem Specification 55A.



CABLE CONSTRUCTION DETAILS							
PART NUMBER 1/	CONDUCTOR SIZE (AWG)	SHIELD SIZE (AWG)	JACKET THICKNESS (in.)		OUTSIDE DIAMETER (in.)		MAXIMUM WEIGHT (lb/1000 ft)
			MINIMUM	NOMINAL	NOMINAL	MAXIMUM	
CTC-0057-24-*	24	38	.006	.008	.123	.129	11.7
CTC-0057-22-*	22	38	.006	.008	.135	.142	14.5
CTC-0057-20-*	20	38	.006	.008	.151	.159	18.7
CTC-0057-18-*	18	38	.006	.008	.173	.182	24.8
CTC-0057-16-*	16	38	.006	.008	.189	.198	30.2

## CABLE RATINGS AND ADDITIONAL REQUIREMENTS

### TEMPERATURE RATING: 200°C

Maximum continuous conductor temperature  
ACCELERATED AGING: 300 ± 3°C for 7 hours  
DIELECTRIC WITHSTAND: 1500 volts (rms), 60 Hz  
FLAMMABILITY: Procedure 1,  
3 seconds (maximum); 3 inches (maximum);  
no flaming of facial tissue

### JACKET ELONGATION AND TENSILE STRENGTH:

Elongation, 50% (minimum)  
Tensile Strength, 5000 lbf/in<sup>2</sup> (minimum)

### JACKET FLAWS:

Spark Test, 1000 volts (rms), 100% test  
Impulse Dielectric Test, 6.0 kV (peak), 100% test

### LOW TEMPERATURE-COLD BEND: -65 ± 2°C for 4 hours

### SHIELD COVERAGE: 85% (minimum)

### VOLTAGE WITHSTAND TEST (Post Environmental):

1000 volts (rms), 60 Hz, 1 minute

### PART NUMBER:

The "\*" in the part numbers above shall be replaced by color code designators with a slash separating the component wire colors and a dash separating the component wire colors from the jacket color. The color of the CHROMEL® shall be shown first.

#### 1/ Example: AWG 22,

Per MIL-STD-687: white and green; white jacket:  
CTC-0057-22-9/5-9

Per ANSI MC96.1: yellow and red; yellow jacket:  
CTC-0057-22-4/2-4

Per British Standard Code BS:  
brown and blue; red jacket:  
CTC-0057-22-1/6-2

The combination of the above thermoelements is referred to as Type KX per ANSI MC96.1.

EMF shall be 4.00 mV (minimum), 4.19 mV (maximum), at 100°C with reference junction corrected to 0°C per ANSI MC96.1, and shall be performed on every length of finished cable.

CHROMEL® and ALUMEL® are federally registered trademarks of Hoskins Manufacturing Company. Alternative conductors, exhibiting the same performance characteristics, may be substituted for one or both of the CHROMEL® and ALUMEL® conductors.

Users should evaluate the suitability of this product for their application. Specifications are subject to change without notice.  
Tyco Electronics also reserves the right to make changes in materials or processing, which do not affect compliance with any specification, without notification to Buyer.

1/ COLORS AND COLOR CODE DESIGNATORS SHALL BE IN ACCORDANCE WITH MIL-STD-681. HOWEVER, DUE TO LENGTH LIMITATIONS OF THE RAYCHEM PART NUMBER, AN ALTERNATIVE COLOR CODE MAY REPLACE MIL-STD-681 COLOR CODE DESIGNATORS. (EXAMPLE: "901/902..." MAY BE REPLACED BY "Axxx".) OTHER CODES AND SUFFIXES MAY BE ADDED TO THE PART NUMBER, AS NECESSARY, TO CAPTURE ANY ADDITIONAL REQUIREMENTS IMPOSED BY THE PURCHASE ORDER.