

CBM-1000 II

Thermal POS Printer



Two-Color Thermal POS Printer



The Citizen CBM-1000 II thermal POS printer fits perfectly in a wide variety of POS applications. It combines high-speed, two-color printing with a compact footprint and an interchangeable serial/parallel/USB port for a reliable, versatile printer. The CBM-1000 II also features a longer-life paper cutter, barcode printing and flash memory for storing and printing logos. And with a spill-resistant top and a quick-and-easy paper drop-in mechanism, the CBM-1000 II is the ideal choice for POS printing.

CITIZEN.

CBM America Corporation

Simply a Better Value.

CBM-1000 II Thermal POS Printer



Reliable, Versatile POS Printing

- 50 percent faster printing speed than CBM-1000
- Dot-addressable two-color and monochrome thermal printing
- Interchangeable serial/parallel/USB port
- Drop-in paper loading
- Barcode printing
- Internal/external power supply configuration
- On/off power switch
- Spill-resistant top
- Permanent logo storage
- 2 drawer kick-out
- Auto paper cutter and tear bar standard
- 80mm or 58mm paper width
- Paper low/paper out sensors
- ESC/POS emulation, OPOS, Windows drivers

Specifications

Printing Method		2-color thermal dot line printing
Print Width		72mm/576 dots (54mm/432 dots)
Dot Density		8 dot/mm
Print Speed		150mm/sec
Number of Columns		Font A: 48/42 (36/30) columns 12 x 24 Font B: 64/56 (48/40) columns (9 x 24)
Character Size		Font A: 1.25 x 3.00mm; Font B: 0.88 x 3.00mm
Logo registration/print		Capable of registering user-defined characters and logos into flash memory.
Barcode Types		UPC-A/E, JAN (EAN), ITF, Codabar, Code 39, Code 93 and Code 128
Line Spacing		4.23mm (1/6 inch), can be set by command (min.: 1/203 inch)
Paper Roll		Thermal paper roll: 80mm (58mm) x 83mm Thermal label paper roll: 80mm (58mm) x 83mm
Label Detection		L-Spec (factory option)
Interface		Centronics Parallel (IEEE 1284 compliant, bi-directional communication), RS-232C Serial, USB and custom
Input Buffer		4K bytes (72 bytes dip switch selectable)
Supply Voltage		S Type: AC 120/130 V±10%; A type/D type: DC 24V±7%
Power Consumption		Approx. 100W
AC Adapter Specifications		Rated input: AC 120 to 240V, 50/60 Hz, 120VA Rated output: DC 24V, 1.9A (Peak 3.5A)
Weight		S type: Approx. 2.0 Kg A type/D type: Approx. 1.4 Kg
Outside Dimensions		S type: 145 (w) x 190 (d) x 157mm (h) A type/D type: 145 (w) x 190 (d) x 114mm (h)
Environment	Operation	Temperature 5-40°C Humidity 35-85%RH
	Storage	Temperature -20-60°C Humidity 10-90%RH

CBM America Corporation

Simply a Better Value.