

# SPECIFICATION CONTROL DRAWING


82A1121

TITLE TWO CONDUCTOR CABLE, SHIELDED, JACKETED, GENERAL PURPOSE, FLEXIBLE, 600 VOLT

Date 5-28-09

Revision E

This specification sheet forms a part of the latest issue of Raychem Specification 80.



CABLE CONSTRUCTION DETAILS							
PART NUMBER 1/	CONDUCTOR SIZE (AWG)	SHIELD SIZE (AWG)	JACKET THICKNESS (in.)		OUTSIDE DIAMETER (in.)		MAXIMUM WEIGHT (lbs/1000 ft.)
			MINIMUM	NOMINAL	NOMINAL	MAXIMUM	
82A1121-28-*	28	38	.005	.008	.091	.097	6.9
82A1121-26-*	26	38	.006	.009	.101	.106	8.5
82A1121-24-*	24	38	.006	.009	.109	.114	10.5
82A1121-22-*	22	38	.007	.010	.123	.129	13.3
82A1121-20-*	20	38	.007	.011	.145	.152	17.8
82A1121-18-*	18	38	.008	.012	.169	.177	25.1
82A1121-16-*	16	38	.009	.013	.201	.211	35.2
82A1121-14-*	14	38	.010	.015	.245	.257	52.7
82A1121-12-*	12	38	.011	.017	.293	.308	75.2
82A1121-10-*	10	36	.013	.020	.375	.394	125.
82A1121-8-*	8	36	.015	.023	.457	.480	186.
82A1121-6-*	6	36	.018	.027	.547	.574	276.
82A1121-4-*	4	34	.023	.035	.732	.769	461.
82A1121-2-*	2	34	.027	.041	.878	.922	669.
82A1121-1-*	1	34	.030	.046	1.008	1.058	840.
82A1121-0-*	0	34	.035	.053	1.164	1.222	1077.
82A1121-00-*	00	34	.038	.057	1.272	1.336	1309.

## CABLE RATINGS AND ADDITIONAL REQUIREMENTS

### TEMPERATURE RATING: 150°C

Maximum continuous conductor temperature

VOLTAGE RATING: 600 volts (rms) at sea level

CROSSLINKING PROOF TEST: 300 ± 3°C for 7 hours

DIELECTRIC WITHSTAND: 1500 volts (rms), 60 Hz

JACKET COLOR: White preferred

JACKET ELONGATION AND TENSILE STRENGTH:

Elongation, 100% (minimum)

Tensile Strength, 3000 lbf/in<sup>2</sup> (minimum)

JACKET FLAWS:

Spark Test, 1500 volts (rms)

Impulse Dielectric Test, 6.0 kV (peak)

### SECANT MODULUS (Test per ASTM D 882):

4.0 x 10<sup>4</sup> lbf/in<sup>2</sup> (maximum),

2% strain, 2 inch jaw separation, 0.2 inch/minute

SHIELD COVERAGE: 85% (minimum)

VOLTAGE WITHSTAND (Post Environmental):

1000 volts (rms), 60 Hz, 1 minute

### PART NUMBER:

The "\*" in the part numbers above shall be replaced by color code designators with a slash separating the component wire colors and a dash separating the component wire colors from the jacket color.

1/ Example: AWG 20, red and white component wires; white jacket:  
82A1121-20-2/9-9

NOTE: Nominal values are for information only.  
Nominal values are not requirements.

Users should evaluate the suitability of this product for their application. Specifications are subject to change without notice.  
Tyco Electronics also reserves the right to make changes in materials or processing, which do not affect compliance with any specification, without notification to Buyer.

1/ COLORS AND COLOR CODE DESIGNATORS SHALL BE IN ACCORDANCE WITH MIL-STD-681. HOWEVER, DUE TO LENGTH LIMITATIONS OF THE RAYCHEM PART NUMBER, AN ALTERNATIVE COLOR CODE MAY REPLACE MIL-STD-681 COLOR CODE DESIGNATORS. (EXAMPLE: "901/902..." MAY BE REPLACED BY "Axxx") OTHER CODES AND SUFFIXES MAY BE ADDED TO THE PART NUMBER AS NECESSARY, TO CAPTURE ANY ADDITIONAL REQUIREMENTS IMPOSED BY THE PURCHASE ORDER.