



Left Side

Connector(s): MPO SECURE (No Pins)
 Mode: MM
 Housing Color: Brown
 Geom. Spec: N/A

Right Side

Connector(s): MPO SECURE (No Pins)
 Mode: MM
 Housing Color: Brown
 Geom. Spec: N/A

Notes:

- 1 IL tested at 1300nm.
- 2 Product and Processing must meet requirements of Tyco Electronics Standard 230-702
- 3 A copy of test data will be placed inside or with the unit package.
- 4 Label 2 will not be present on any cable assembly less than 5 meters long.
- 5 The cable meets or exceeds the requirements of GR-409-CORE for both RISER and PLENUM applications.
- 6 The cable meets or exceeds the UL requirements for both RISER and PLENUM applications.

THIS INFORMATION IS CONFIDENTIAL AND PROPRIETARY TO TYCO ELECTRONICS CORPORATION. IT IS THE PROPERTY OF TYCO ELECTRONICS CORPORATION AND IS NOT TO BE DISCLOSED TO ANY OTHER PERSON OR ENTITY WITHOUT THE WRITTEN AUTHORIZATION OF TYCO ELECTRONICS CORPORATION, HARRISBURG, PENNSYLVANIA

LOC	
CE	
DIST	
16	

A	Rev Per EC#	RELEASE	7/28/2008	-	JD				
P	LTR	REVISION RECORD	DATE	DN	APVD				

DIMENSIONS:	TOLERANCES UNLESS OTHERWISE SPECIFIED:
meters	0 PLC ± .
	1 PLC ± .
	2 PLC ± .
	3 PLC ± .
	4 PLC ± .

Restricted To:

DWG	Cable Assy Configurator	MATERIAL		HEAT TREAT	
CHK	Joe Davis	Tyco Electronics, Inc. Harrisburg, PA 17105-3608			
APVD	Joe Davis				
NAME	FO C/A - 24 fiber, 50/125, OFNR-OFNP, MPO SECURE (No Pins) to MPO SECURE (No Pins)				
SCALE	NTS	SIZE	A2	DRAWING NO	C- 1918761
SHEET	1 of 5	REV	A		

D
C
B
A

