


141-0002-0002 Product Details

Live Product Chat US Only
8:30am - 5pm ET, Mon - Fri



Ultra Miniature (LEPRA/CON) RF Connectors

Always EU RoHS/ELV Compliant ([Statement of Compliance](#))

Product Highlights:

- Connector
- Receptacle
- Terminate To Coaxial Cable
- Coupler Style = Threaded
- Coaxial Cable Termination Type = Solder

[View all Features](#) | [Find Similar Products](#)

141-0002-0002
(1466330-1)

TE Part Number: 1466330-1

[Active](#)

[Add to Part List](#)

Quick Links

- ▶ [Check Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

Documentation & Additional Information

Product Drawings:

- None Available

Catalog Pages/Data Sheets:

- None Available

Product Specifications:

- None Available

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files:

- None Available

Additional Information:

- [Product Line Information](#)

Related Products:

- [Tooling](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Product Type = Connector
- Gender = Receptacle
- Body Style = Straight
- Grade = Commercial
- Body Material = Brass
- Panel Thickness (mm [in]) = 2.36 [0.093]

Mechanical Attachment:

- Panel Attachment = With
- Panel Attachment Style = Front Mount
- Panel Attachment Method = Lockwasher and Nut

Electrical Characteristics:

- Connector Impedance (Ω) = 50

Termination Related Features:

- Coaxial Cable Termination Type = Solder

Body Related Features:

- Coupler Style = Threaded
- Terminal Style = Solder Pot
- Locking Interface = Without
- Body Plating = Gold per MIL-G-45204, Type II, Grade C, Class 1

Contact Related Features:

- Center Contact Plating = Gold per MIL-G-45204, Type II, Grade C, Class 1

Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C, Reflow solder capable to 245°C, Reflow solder capable to 260°C, Pin-in-Paste capable to 245°C, Pin-in-Paste capable to 260°C
- RoHS/ELV Compliance History = Always was RoHS compliant

Conditions for Usage:

- Terminate To = Coaxial Cable

Other:

- Brand = Microdot