




# MULTIPLE CONFIGURATION PCB HEADERS & RECEPTACLES



✓ Active

↓ **PRODUCT DRAWING**  
English

↓ **3D PDF**

## TE CONNECTIVITY (TE) 13 MODII HDR SRST B/A .100CL

AMPMODU | AMPMODU Headers

1-102976-3

TE Internal Number: 1-102976-3

Not EU RoHS or ELV Compliant

[Find Compliant Alternatives](#)

Applies To **Printed Circuit Board**

Connector Style **Plug**

Centerline **2.54 mm [ .1 in ]**

Number of Positions **13**

Header Type **Breakaway**

### Product Drawings

[HEADER ASSY, MOD II, BREAKAWAY, SINGLE ROW, .100 CL, VERTICAL, WITH .025 SQUARE POSTS](#)

PDF  
English

### CAD Files

[Customer View Model](#)

2D\_DXF.ZIP  
English

[Customer View Model](#)

3D\_IGS.ZIP  
English

[Customer View Model](#)

3D\_STP.ZIP  
English

[3D PDF](#)

PDF  
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

### Product Type Features

Applies To

**Printed Circuit Board**

Connector Style

**Plug**

PCB Mounting Orientation

**Vertical**

Connector Type

**Header**

Row-to-Row Spacing

**2.54 mm [ .1 in ]**

Stabilizers

**Without**

Strain Relief

**Without**

	Strain Relief	<b>Without</b>
	Board Standoff	<b>Without</b>
	Product Type	<b>Connector</b>
	Gasket	<b>Without</b>
Configuration Features	Number of Positions	<b>13</b>
	Number of Rows	<b>1</b>
	Keyed	<b>No</b>
	Selectively Loaded	<b>No</b>
Electrical Characteristics	Dielectric Withstanding Voltage	<b>750 V</b>
Body Features	Header Type	<b>Breakaway</b>
	Post Size	<b>.64 mm [ .025 in ]</b>
Contact Features	Contact Protection	<b>Without</b>
	Contact Shape	<b>Square</b>
	Contact Type	<b>Pin</b>
	Contact Base Material	<b>Phosphor Bronze</b>
	Contact Mating Area Plating Thickness (µin)	<b>30</b>
	Solder Tail Contact Plating Material	<b>Tin-Lead over Nickel</b>
	Contact Mating Area Plating Material	<b>Gold</b>
	Contact Current Rating (A)	<b>3</b>
Termination Features	Termination Post Length	<b>3.18 mm [ .125 in ]</b>
	Termination End Plating Thickness (µin)	<b>100 – 200</b>
	Termination End Plating Material	<b>Tin-Lead Over Nickel</b>
	Termination Method to PC Board	<b>Through Hole</b>
Mechanical Attachment	PCB Mounting Style	<b>Through Hole</b>
	PCB Mount Retention	<b>Without</b>
	Panel Mount Retention	<b>Without</b>
	Mating Connector Lock	<b>Without</b>
Housing Features	Centerline	<b>2.54 mm [ .1 in ]</b>
	Housing Color	<b>Black</b>
	Housing Material	<b>Thermoplastic</b>

Dimensions	Mating Post Length	<b>8.08 mm [ .318 in ]</b>
Usage Conditions	Operating Temperature Range (°C)	<b>-65 – 105</b>
	High Temperature Housing	<b>No</b>
Operation/Application	High Speed Serial Data Connector	<b>No</b>
Industry Standards	UL Flammability Rating	<b>UL 94V-0</b>
	Approved Standards	<b>CSA LR7189, UL E28476</b>
Packaging Features	Packaging Quantity	<b>120</b>
	Packaging Method	<b>Carton</b>
Other	Comment	<b>Headers may be broken to desired number of positions using Hand Tool No. 91406-1, or Tool Kit No. 314818-1. Other tail lengths are available, consult TE Connectivity.</b>
Product Compliance	<a href="#">Statement of Compliance PDF</a> <a href="#">VIEW ALL PRODUCT COMPLIANCE</a>	

Products - 1 Results

[View All](#)

Compare 0/10 

Relation Type ▼

RELATIONSHIP

## Mating Products

Used to identify Mating Parts

[See All Mating Products](#)

PRODUCT - MATING PRODUCTS



Connectors - FFC Connectors  
FFC | FFC

**013 HOUSING FFC RCPT**  
**100CL SR - 1-487378-2**

TE INTERNAL NUMBER: 1-487378-2

✓ Active

Always EU RoHS/ELV Compliant

Connector Type **Housing**

Connector Style **Receptacle**

Centerline **2.54 mm**

Number of Positions **13**

Number of Rows **1**

