



# Chip Inductor – 1008HT Series (2520)

- Low-profile inductors are 60% the height of our other 1008 size parts.
- They feature high SRFs and very high Q factors.

Coilcraft **Designer's Kit C322** contains samples of all 5% inductance tolerance parts. To order, please contact Coilcraft or order on-line at <http://order.coilcraft.com>.

Part number <sup>1</sup>	Inductance <sup>2</sup> (nH)	Percent tolerance <sup>3</sup>	Q min <sup>4</sup>	SRF min <sup>5</sup> (MHz)	DCR max <sup>6</sup> (Ohms)	Irms <sup>7</sup> (mA)
1008HT-3N3TJL_	3.3 @ 250 MHz	<b>5</b>	65 @ 1500 MHz	7900	0.025	1000
1008HT-6N8TJL_	6.8 @ 250 MHz	<b>5</b>	70 @ 1500 MHz	5500	0.05	1000
1008HT-7N2TJL_	7.2 @ 250 MHz	<b>5</b>	70 @ 1500 MHz	4800	0.05	1000
1008HT-12NTJL_	12 @ 250 MHz	<b>5</b>	55 @ 700 MHz	3800	0.065	1000
1008HT-15NTJL_	15 @ 250 MHz	<b>5</b>	55 @ 700 MHz	2800	0.08	1000
1008HT-18NTJL_	18 @ 250 MHz	<b>5</b>	55 @ 500 MHz	3000	0.09	1000
1008HT-22NTJL_	22 @ 250 MHz	<b>5</b>	55 @ 500 MHz	2600	0.11	950
1008HT-27NT_L_	27 @ 250 MHz	<b>5,2</b>	55 @ 500 MHz	2400	0.13	850
1008HT-33NT_L_	33 @ 200 MHz	<b>5,2</b>	55 @ 350 MHz	2000	0.135	760
1008HT-39NT_L_	39 @ 200 MHz	<b>5,2</b>	55 @ 350 MHz	1900	0.17	700
1008HT-47NT_L_	47 @ 200 MHz	<b>5,2,1</b>	55 @ 350 MHz	1500	0.18	660
1008HT-56NT_L_	56 @ 150 MHz	<b>5,2,1</b>	50 @ 300 MHz	1500	0.18	620
1008HT-68NT_L_	68 @ 150 MHz	<b>5,2,1</b>	50 @ 300 MHz	1500	0.23	550
1008HT-82NT_L_	82 @ 150 MHz	<b>5,2,1</b>	40 @ 250 MHz	1300	0.35	500
1008HT-R10T_L_	100 @ 100 MHz	<b>5,2,1</b>	40 @ 250 MHz	1200	0.64	420
1008HT-R12T_L_	120 @ 100 MHz	<b>5,2,1</b>	40 @ 200 MHz	1090	0.55	350
1008HT-R14T_L_	140 @ 100 MHz	<b>5,2,1</b>	40 @ 200 MHz	1100	0.70	320
1008HT-R15T_L_	150 @ 100 MHz	<b>5,2,1</b>	40 @ 200 MHz	960	0.75	300
1008HT-R18T_L_	180 @ 50 MHz	<b>5,2,1</b>	40 @ 200 MHz	920	1.02	250
1008HT-R22T_L_	220 @ 50 MHz	<b>5,2,1</b>	34 @ 100 MHz	750	1.15	250
1008HT-R24T_L_	240 @ 50 MHz	<b>5,2</b>	32 @ 100 MHz	800	1.15	250
1008HT-R27T_L_	270 @ 50 MHz	<b>5,2</b>	32 @ 100 MHz	770	1.25	250
1008HT-R33T_L_	330 @ 25 MHz	<b>5,2</b>	32 @ 100 MHz	635	1.35	250
1008HT-R39T_L_	390 @ 25 MHz	<b>5,2</b>	32 @ 100 MHz	555	1.45	250
1008HT-R47T_L_	470 @ 25 MHz	<b>5,2</b>	32 @ 100 MHz	530	1.65	240
1008HT-R56T_L_	560 @ 25 MHz	<b>5,2</b>	32 @ 100 MHz	485	1.90	240

1. When ordering, specify **tolerance, termination and packaging** codes:

1008HT-R56TJLC

**Tolerance:** F = 1% G = 2% J = 5%

(Table shows stock tolerances in bold.)

**Termination:** L = RoHS compliant silver-palladium-platinum-glass frit.  
Special order: T = RoHS tin-silver-copper (95.5/4/0.5)  
or S = non-RoHS tin-lead (63/37).

**Packaging:** C = 7" machine-ready reel. EIA-481 embossed plastic tape (2000 parts per full reel).

B = Less than full reel. In tape, but not machine ready.  
To have a leader and trailer added (\$25 charge),  
use code letter C instead.

D = 13" machine-ready reel. EIA-481 embossed plastic tape (7500 parts per full reel).

2. Inductance measured using a Coilcraft SMD-A fixture in an Agilent/HP 4286A impedance analyzer with Coilcraft-provided correlation pieces.

3. Tolerances in bold are stocked for immediate shipment.

4. Q measured using an Agilent/HP 4291A with an Agilent/HP 16193 test fixture.

5. SRF measured using an Agilent/HP 8720D network analyzer and a Coilcraft SMD-D test fixture.

6. DCR measured on a Cambridge Technology micro-ohmmeter and a Coilcraft CCF840 test fixture.

7. Current that causes a 15°C temperature rise from 25°C ambient. This information is for reference only and does not represent absolute maximum ratings.

8. Electrical specifications at 25°C.

See Color Coding section for part marking data.

Refer to Doc 362 "Soldering Surface Mount Components" before soldering.



www.coilcraft.com

US +1-847-639-6400 sales@coilcraft.com  
UK +44-1236-730595 sales@coilcraft-europe.com  
Taiwan +886-2-2264 3646 sales@coilcraft.com.tw  
China +86-21-6218 8074 sales@coilcraft.com.cn  
Singapore +65-6484 8412 sales@coilcraft.com.sg

Document 169-1 Revised 10/12/15

© Coilcraft Inc. 2015

This product may not be used in medical or high risk applications without prior Coilcraft approval. Specification subject to change without notice. Please check web site for latest information.


**COILCRAFT** ACCURATE  
**PRECISION** REPEATABLE  
MEASUREMENTS  
SEE WEB SITE **TEST FIXTURES**





# Chip Inductor – 1008HT Series (2520)

**S-Parameter files**  
ON OUR WEB SITE  
**SPICE models**  
ON OUR WEB SITE

## Typical Q vs Frequency



## Typical L vs Frequency



A	B	C	E	F	G	H	I	J	
max	max	max							inches
0.105	0.095	0.045	0.080	0.020	0.060	0.100	0.040	0.050	
2.67	2.41	1.14	2.03	0.51	1.52	2.54	1.02	1.27	mm

**Note:** Height dimension is before optional solder application. For maximum height dimension including solder, add 0.006 in / 0,152 mm.

**Core material** Ceramic

**Terminations** RoHS compliant silver-palladium-platinum-glass frit. Other terminations available at additional cost.

**Weight** 16.0– 17.6 mg

**Ambient temperature** –40°C to +125°C with Irms current

**Maximum part temperature** +140°C (ambient + temp rise).

**Storage temperature** Component: –40°C to +140°C.

Tape and reel packaging: –40°C to +80°C

**Resistance to soldering heat** Max three 40 second reflows at +260°C, parts cooled to room temperature between cycles

**Temperature Coefficient of Inductance (TCL)** +25 to +125 ppm/°C

**Moisture Sensitivity Level (MSL)** 1 (unlimited floor life at <30°C / 85% relative humidity)

**Failures in Time (FIT) / Mean Time Between Failures (MTBF)**

One per billion hours / one billion hours, calculated per Telcordia SR-332

**Packaging** 2000/7" reel; 7500/13" reel Plastic tape: 8 mm wide, 0.23 mm thick, 4 mm pocket spacing, 1.14 mm pocket depth

**PCB washing** Tested to MIL-STD-202 Method 215 plus an additional aqueous wash. See [Doc787\\_PCB\\_Washing.pdf](#).



**US** +1-847-639-6400 sales@coilcraft.com  
**UK** +44-1236-730595 sales@coilcraft-europe.com  
**Taiwan** +886-2-2264 3646 sales@coilcraft.com.tw  
**China** +86-21-6218 8074 sales@coilcraft.com.cn  
**Singapore** + 65-6484 8412 sales@coilcraft.com.sg

Document 169-2 Revised 10/12/15

© Coilcraft Inc. 2015

This product may not be used in medical or high risk applications without prior Coilcraft approval. Specification subject to change without notice. Please check web site for latest information.

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

## Coilcraft:

[1008HT-R15TJLB](#) [1008HT-R27TJLB](#) [1008HT-R14TGLC](#) [1008HT-R56TGLC](#) [1008HT-15NTJLC](#) [1008HT-47NTGLC](#)  
[1008HT-R33TGLC](#) [1008HT-27NTGLB](#) [1008HT-56NTJLB](#) [1008HT-R12TJLC](#) [1008HT-R24TJLC](#) [1008HT-R24TGLB](#)  
[1008HT-12NTJLB](#) [1008HT-R22TGLC](#) [1008HT-33NTGLB](#) [1008HT-39NTJLC](#) [1008HT-R39TJLB](#) [1008HT-7N2TJLC](#)  
[1008HT-33NTJLC](#) [1008HT-22NTJLC](#) [1008HT-82NTGLC](#) [1008HT-6N8TJLC](#) [1008HT-R18TGLB](#) [1008HT-R39TGLB](#)  
[1008HT-R10TJLB](#) [1008HT-68NTJLB](#) [1008HT-27NTJLC](#) [1008HT-R47TJLB](#) [1008HT-3N3TJLB](#) [1008HT-R24TGLC](#)  
[1008HT-3N3TJLC](#) [1008HT-R47TJLC](#) [1008HT-R15TGLB](#) [1008HT-22NTJLB](#) [1008HT-R12TGLC](#) [1008HT-18NTJLB](#)  
[1008HT-R39TJLC](#) [1008HT-R27TGLB](#) [1008HT-R33TJLB](#) [1008HT-68NTJLC](#) [1008HT-R47TGLC](#) [1008HT-R10TJLC](#)  
[1008HT-R14TJLC](#) [1008HT-R22TJLC](#) [1008HT-47NTJLB](#) [1008HT-R47TGLB](#) [1008HT-R56TGLB](#) [1008HT-15NTJLB](#)  
[1008HT-R22TJLB](#) [1008HT-56NTGLC](#) [1008HT-R15TJLC](#) [1008HT-R14TGLB](#) [1008HT-R22TGLB](#) [1008HT-39NTJLB](#)  
[1008HT-R12TJLB](#) [1008HT-R56TJLC](#) [1008HT-47NTGLB](#) [1008HT-7N2TJLB](#) [1008HT-33NTJLB](#) [1008HT-R56TJLB](#)  
[1008HT-R33TGLB](#) [1008HT-R39TGLC](#) [1008HT-12NTJLC](#) [1008HT-6N8TJLB](#) [1008HT-33NTGLC](#) [1008HT-R15TGLC](#)  
[1008HT-R18TGLC](#) [1008HT-27NTGLC](#) [1008HT-82NTJLC](#) [1008HT-39NTGLC](#) [1008HT-68NTGLC](#) [1008HT-R10TGLC](#)  
[1008HT-R27TGLC](#) [1008HT-82NTGLB](#) [1008HT-18NTJLC](#) [1008HT-R10TGLB](#) [1008HT-R24TJLB](#) [1008HT-R33TJLC](#)  
[1008HT-R18TJLC](#) [1008HT-R14TJLB](#) [1008HT-R27TJLC](#) [1008HT-56NTGLB](#) [1008HT-27NTJLB](#) [1008HT-R18TJLB](#)  
[1008HT-47NTJLC](#) [1008HT-39NTGLB](#) [1008HT-R12TGLB](#) [1008HT-82NTJLB](#) [1008HT-56NTJLC](#) [1008HT-68NTGLB](#)