

# Contact insert module - HC-M-04-KT-M - 1417371


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



HEAVYCON contact insert module, 4-pos., for HC-M-04-BU-KOAX... coaxial contacts



## Key Commercial Data

Packing unit	5 STK
Minimum order quantity	5 STK
GTIN	 4 055626 112534
GTIN	4055626112534

## Technical data

### Dimensions

Height	31.5 mm
Width	34.2 mm
Length	14.6 mm

### Electrical characteristics

Note	For HEAVYCON housing type B6 to B48, HC-M-MHR... hinged retaining frame required, HC-M-04-KOAX... crimp contacts (crimp contacts not supplied as standard)
Rated voltage (III/3)	50 V
Rated current	1.5 A
Rated surge voltage	0.8 kV
Contact resistance, phase conductor	≤ 3 mΩ
Contact resistance, inner conductor	≤ 10 mΩ
Insulation resistance	≥ 10 GΩ
Connection profile	4xKOAX

### Ambient conditions

Ambient temperature (operation)	-40 °C ... 125 °C
---------------------------------	-------------------

# Contact insert module - HC-M-04-KT-M - 1417371

## Technical data

### Mechanical characteristics

Insertion/withdrawal cycles	≥ 500
-----------------------------	-------

### General

Series	HC-M-04-KOAX
Color	light gray
Number of module slots	1
Connection method	Soldering and crimp connection
Flammability rating according to UL 94	V0
Degree of pollution	3
Overvoltage category	III
Assembly instructions	For housing heights ≥ 52 mm. Plug-in connections may only be operated only when there is no load/voltage.
Connection	For HC-M-04-BU-KOAX... contacts

### Material data

Contact material	Copper alloy
Contact surface material	AU
Contact carrier material	PC

### Standards and Regulations

Flammability rating according to UL 94	V0
--	----

## Approvals

### Approvals

---

#### Approvals

EAC

---

#### Ex Approvals

---

### Approval details

EAC		7500651.22.01.00246
-----	---	---------------------

---

Phoenix Contact 2017 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>