

Datasheet

RS Pro ON Delay Single Time Delay Relay, Screw, 0.3 s → 30 h, SPDT, 1 Contacts, SPCO, 24 V ac/dc, 240 V ac
RS Stock No: **896-6810**



Product Details

RS Pro ON delay single time delay relay is a dual voltage, single function timer. This relay is compact in size and suitable for DIN rail mounting. It comes with a terminal screw and it has a time range of 0.3 s to 30 h with SPDT and SPCO switch configuration. It has 1 contact and supply voltage of 24 V ac/dc and 240 V ac.

Features and Benefits

- 17.5 mm wide
- DIN rail mounting
- Integrated dual voltage
- On delay timing function
- LED indications for power and relay status
- SPCO output relay
- 0.3 s to 30 hours timing range
- Wide supply voltage range
- IP20 (terminals), IP40 (enclosure) protection

Specifications:

Number of Timer Functions	Single
Power Supply	External
Switch Configuration	SPCO
Time Increment	Seconds
Depth	58.5 mm
Length	17.5 mm
Maximum Operating Temperature	+55°C
Minimum Operating Temperature	-10°C
Number of Contacts	1
Width	90 mm
Contact Configuration	CO
Current Maximum	5 A
Current Minimum	0.1 A
Maximum Voltage	24 V ac/dc, 240 V ac
Mode of Operation	On Delay
Mounting Type	DIN Rail
Supply Voltage	24 V ac/dc, 240 V ac
Terminal Type	Screw
Time Delay	100 ms
Time Range	0.3 s to 30 h
IP Rating	IP20, IP40