

This document was generated on 02/23/2021

## PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

**Part Number:** 1731620338

Status: **Active** 

Overview: Nano-Pitch I/O Interconnect System

Nano-Pitch I/O Receptacle, Straight, Extra Duty Through Hole, 3.00mm Tail Length, **Description:** 

with Cap, 80 Circuits

**Documents:** 

Application Specification AS-173162-0001-001 (PDF) 3D Model Packaging Specification PK-173307-0001-001 (PDF) 3D Model (PDF)

Drawing (PDF) RoHS Certificate of Compliance (PDF)

Product Specification PS-173162-0001-001 (PDF)

**Agency Certification** 

E29179

General

I/O Connectors **Product Family** Series 173162 **Application** Wire-to-Board Component Type Receptacle

Overview Nano-Pitch I/O Interconnect System

Nano-Pitch I/O **Product Name** 

Type N/A

UPC 889056676663

**Physical** 

Circuits (Loaded) 80 Circuits (maximum) 80 Color - Resin Black Durability (mating cycles max) 250 Flammability 94V-0 Gender Receptacle Keying to Mating Part None Lock to Mating Part Yes Material - Metal Copper Alloy

Material - Plating Mating Gold Material - Plating Termination

Material - Resin High Temperature Thermoplastic

Net Weight 1.680/g Number of Rows 2 Orientation Vertical PCB Locator Yes **PCB** Retention Yes PCB Thickness - Recommended 1.57mm

**Embossed Tape on Reel** Packaging Type

**Panel Mount** No Pitch - Mating Interface 0.50mm Pitch - Termination Interface 0.50mm Plating min - Mating 0.762µm Plating min - Termination 2.540µm Polarized to Mating Part Yes Polarized to PCB Yes Ports

Temperature Range - Operating -40° to +80°C Termination Interface: Style Through Hole

Waterproof / Dustproof No



**EU ELV** 

**Not Relevant** 

**EU RoHS China RoHS** 

Compliant **REACH SVHC** Not Contained Per -D(2020)9139-DC (19 Jan 2021)

Halogen-Free **Status** 

Low-Halogen

For more information, please visit Contact US

China ROHS Green Image Not Relevant ELV RoHS Phthalates Not Contained

Search Parts in this Series

173162 Series

**Mates With** 

Nano-Pitch I/O Cable Assembly 205058

**Electrical** 

Current - Maximum per Contact 0.5A
Grounding to Panel None
Shielded No

Voltage - Maximum 30V AC (RMS)/DC

**Material Info** 

**Reference - Drawing Numbers** 

Application Specification AS-173162-0001-001
Electrical Model Document EE-173162-0010
Packaging Specification PK-173307-0001-001
Product Specification PS-173162-0001-001
S-Parameter Model SP-173162-0010
Sales Drawing SD-173162-0002-001

This document was generated on 02/23/2021

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION