

## 3M™ Adjustable Wrist Straps 2204, 2214, 2224

Adjustable Wrist Straps provide a comfortable, custom fit. One size adjusts to most any size wrist to provide reliable, 360-degree protection. A 1 megohm resistor is built into the ground cord. Available with 1/8 in. (4 mm) snap end. Adjust band over a range of diameters, 1.7 in. – 3.5 in. Meets the requirements of ANSI/ESD S20.20-2014, EIA 625.



**! WARNING:**  
All 3M Wrist Straps should not be used in areas where the individual may come in contact with electrical circuitry exceeding 250 volts.

Specifications - Band	Typical Value
Fabric	Elastic Nylon
Resistance	< 500 ohms
Contact	360 degrees around wrist
Color	Burgundy
Snap	4 mm
Snap Release	< 2 lbs.
Back Plate	Stainless Steel
Markings	UL
Specifications - Cord	Typical Value
Length	5 or 10 feet
Resistance	1 megohm
Flex life	≥ 16,000 flexes
Color	Black
Snap	4 mm
Part Numbers	
2204	3M™ Adjustable Fabric Wrist Band, in burgundy color
2214	3M™ Adjustable Fabric Wrist Band, in burgundy color, with coiled cord 5 ft. (1.5 m). Includes alligator clip
2224	3M™ Adjustable Fabric Wrist Band, in burgundy color, with coiled cord 10 ft. (3 m). Includes alligator clip

\*Meets the requirements of ANSI/ESD S1.1-2006, S20.20-2014, EIA 625

### 3M™ Adjustable Wrist Straps 2204, 2214, 2224

3M is a trademark of 3M Company.

#### Important Notice

All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

#### Warranty; Limited Remedy; Limited Liability.

This product will be free from defects in material and manufacture for one year from the time of purchase. **3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. **Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.**



#### Electronics Materials Solutions Division Static Control Products

926 JR Industrial Drive  
Sanford, NC 27332-9733  
Toll-Free: 866-722-3736  
International: 919-718-0000  
Email: [3mstaticinfo@mmm.com](mailto:3mstaticinfo@mmm.com)  
[www.3mstatic.com](http://www.3mstatic.com)

Please recycle. Printed in USA.  
© 3M 2014. All rights reserved.  
78-9102-1845-8 JHA

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

SCS:

[2224](#) [2214](#) [2204](#)