

# Interface converter - PSM-EG-RS232/RS232-P/4K - 2761444

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Interface converter, for the electrical isolation of two RS-232 interfaces, 4 channels, integrated DTE/DCE switch-over, DIN-rail mountable

The illustration shows a variant of the V.24 (RS-232)/RS-422 converter



## Key Commercial Data

Packing unit	1 pc
GTIN	
Weight per Piece (excluding packing)	251.05 g
Custom tariff number	85176200
Country of origin	Germany

## Technical data

### Note

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---

### Dimensions

Width	45 mm
Height	75 mm
Depth	110 mm

### Ambient conditions

Ambient temperature (operation)	0 °C ... 50 °C
---------------------------------	----------------

### General

Bit delay	≤ 3 µs
Bit distortion	≤ 5 %
Electrical isolation	VCC // V.24 (RS-232) (A) // V.24 (RS-232) (B)
Test voltage data interfaces	2.5 kV AC

# Interface converter - PSM-EG-RS232/RS232-P/4K - 2761444

## Technical data

### General

Test voltage data interface/power supply	2.5 kV AC
	2.5 kV
Electromagnetic compatibility	Conformance with EMC Directive 2004/108/EC
Net weight	251.05 g
Housing material	ABS
Color	green

### Power supply

Nominal supply voltage	24 V DC $\pm$ 20 %
Typical current consumption	130 mA (24 V DC)

### Serial interface

Transmission length	15 m (twisted pair)
Conductor cross section flexible min.	0.2 mm <sup>2</sup>
Conductor cross section flexible max.	2.5 mm <sup>2</sup>
Conductor cross section AWG min.	24
Conductor cross section AWG max.	14

## Classifications

### eCl@ss

eCl@ss 4.0	27250312
eCl@ss 4.1	27250312
eCl@ss 5.0	27242208
eCl@ss 5.1	27242208
eCl@ss 6.0	27242208
eCl@ss 7.0	27242208

### ETIM

ETIM 2.0	EC000310
ETIM 3.0	EC000310
ETIM 4.0	EC000310
ETIM 5.0	EC000310

### UNSPSC

UNSPSC 6.01	30211506
UNSPSC 7.0901	39121008
UNSPSC 11	39121008
UNSPSC 12.01	39121008
UNSPSC 13.2	43201553

# Interface converter - PSM-EG-RS232/RS232-P/4K - 2761444

## Approvals

Approvals

---

Approvals

EAC

---

Ex Approvals

---

Approvals submitted

---

Approval details

EAC
-----

## Accessories

Accessories

Adapter cable

Data cable - PSM-KA 9 SUB 25/BB/2METER - 2761059



RS-232 cable, 9-pos. D-SUB socket 25-pos on D-SUB socket

---

Data cable - PSM-KA9SUB9/BB/2METER - 2799474



RS-232 cable, 9-pos. D-SUB socket on 9-pos. D-SUB socket, 9-wire, 1:1

---

Data plug

D-SUB bus connector - SUBCON 9/M-SH - 2761509



D-SUB connector, 9-pos., male connector, one cable entry <math>< 35^\circ</math>, universal type for all systems, pin assignment: 1, 2, 3, 4, 5, 6, 7, 8, 9 to screw connection terminal block

## Interface converter - PSM-EG-RS232/RS232-P/4K - 2761444

### Accessories

---

#### Interface converter

Interface converter - PSM-ME-RS232/RS232-P - 2744461



Interface converter, for the isolation of RS-232 (V.24) interfaces, 4 channels, rail-mountable

---

#### Mounting material

Components of electronic housing - ME-SAS - 2853899



Shield connection clamp for printed circuit terminal block

---

#### Screwdriver tools

Screwdriver - SZF 1-0,6X3,5 - 1204517



Actuation tool, for ST terminal blocks, also suitable for use as a bladed screwdriver, size: 0.6 x 3.5 x 100 mm, 2-component grip, with non-slip grip

---