

## Active module - UM- D37SUB/M/HC3/16DO/MR/SI/Z - 2900190

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



16-channel relay module for Honeywell C300 output modules. The module is controlled by the control system via 37-pos. D-SUB or 50-pos. FLK. A screw connection with knife disconnection is available in the field. Module width: 227 mm



### Key commercial data

Packing unit	1
GTIN	4 046356 495998
Custom tariff number	85369010

### Technical data

#### Note

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---

#### Dimensions

Width	227 mm
Height	128 mm

#### Ambient conditions

Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C

#### Output data

Contact type	Single contact, 1-PDT
Contact material	AgSnO
Maximum switching voltage	250 V AC/DC
Minimum switching voltage	12 V AC/DC
Limiting continuous current	4 A

#### General

No. of channels	16
Mounting position	any

# Active module - UM- D37SUB/M/HC3/16DO/MR/SI/Z - 2900190

## Technical data

### General

Standards/regulations	DIN EN 50178
Pollution degree	2
Surge voltage category	III

### Connection data for connection 1

Connection name	Controller level
Number of connections	1
Connection method	D-SUB pin strip
Number of positions	37

### Connection data for connection 2

Connection name	Field level
Connection method	Spring-cage connection
Conductor cross section solid min.	0.2 mm <sup>2</sup>
Conductor cross section solid max.	4 mm <sup>2</sup>
Conductor cross section stranded min.	0.2 mm <sup>2</sup>
Conductor cross section stranded max.	2.5 mm <sup>2</sup>
Conductor cross section AWG/kcmil min.	24
Conductor cross section AWG/kcmil max.	12
Stripping length	8 mm

### Connection data for connection 3

Connection name	Controller level
Number of connections	1
Connection method	Flat-ribbon cable connector in acc. with IEC 60603-13
Number of positions	50

### Supported controller

Corresponding control	HONEYWELL C300
Corresponding I/O card	TDOB01 (non-redundant)
	TDOB11 (redundant)

## Classifications

### eCl@ss

eCl@ss 4.0	27250313
eCl@ss 4.1	27250313
eCl@ss 5.0	27250313
eCl@ss 5.1	27250313
eCl@ss 6.0	27242608
eCl@ss 7.0	27141152

## Active module - UM- D37SUB/M/HC3/16DO/MR/SI/Z - 2900190

### Classifications

#### ETIM

ETIM 2.0	EC001434
ETIM 3.0	EC001604
ETIM 4.0	EC001604
ETIM 5.0	EC002780

#### UNSPSC

UNSPSC 6.01	30211824
UNSPSC 7.0901	39121421
UNSPSC 11	39121421
UNSPSC 12.01	39121421
UNSPSC 13.2	39121421

### Accessories

#### Accessories

#### Fuse

Fuse - VF-SI/TR5/4AT - 2900998



Plug-in fuse (TR5<sup>®</sup>), nominal current: 4 A, tripping characteristic: slow-blow (T), packing volume per unit: 8 pcs.