


Output module - UM-2KS50/ 8DO/RS/Z/C-L/SO225 - 2319485

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



8-channel digital output module with spring-cage connection. The power supply unit and the 50-pos. strip are designed redundantly. Suitable for Yokogawa card SDV 531 and SDV 531L.



Key commercial data

Packing unit	1 pc
GTIN	
Weight per Piece (excluding packing)	573.9 g
Custom tariff number	85369010
Country of origin	Germany
Note	Made to Order (non-returnable)

Technical data

Note

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---

Dimensions

Width	152.5 mm
Height	126 mm
Depth	97 mm

Ambient conditions

Ambient temperature (operation)	-20 °C ... 55 °C
---------------------------------	------------------

General

Note	Voltage monitoring on the module does not work in combination with upstream HESILED fuse terminal blocks with integrated LED display.
Max. permissible operating voltage	30 V DC
Max. perm. current (per branch)	600 mA
Max. permissible current (all branches)	6.3 A
Mounting position	any

Output module - UM-2KS50/ 8DO/RS/Z/C-L/SO225 - 2319485

Technical data

General

Designation	Air and creepage distances
Standards/regulations	DIN EN 50178
Rated insulation voltage	50 V
Rated surge voltage	0.8 kV (basic insulation)
Pollution degree	2
Surge voltage category	III

Connection data for connection 1

Connection name	Field level
Connection method	Spring-cage connection
Number of positions	16
Conductor cross section solid min.	0.2 mm ²
Conductor cross section solid max.	4 mm ²
Conductor cross section stranded min.	0.2 mm ²
Conductor cross section stranded max.	2.5 mm ²
Conductor cross section AWG/kcmil min.	24
Conductor cross section AWG/kcmil max	12

Connection data for connection 2

Connection name	Controller level
Number of connections	2
Connection method	Yokogawa KS-compatible
Number of positions	50

Supported controller

Controller	YOKOGAWA ProSafe-RS
- suitable I/O card	SDV531/-L

Classifications

eCl@ss

eCl@ss 4.0	27250313
eCl@ss 4.1	27250313
eCl@ss 5.0	27250313
eCl@ss 5.1	27250313
eCl@ss 6.0	27069203
eCl@ss 7.0	27069203

ETIM

ETIM 2.0	EC001434
ETIM 3.0	EC001604
ETIM 4.0	EC001437

Output module - UM-2KS50/ 8DO/RS/Z/C-L/SO225 - 2319485

Classifications

ETIM

ETIM 5.0	EC001437
----------	----------

UNSPSC

UNSPSC 6.01	30211824
UNSPSC 7.0901	39121421
UNSPSC 11	39121421
UNSPSC 12.01	39121421
UNSPSC 13.2	39121421

Accessories

Accessories

System cable

Cable - FLK 50-PA/EZ-DR/KS/ 200/YOC - 2314396



Assembled round cable with two molded 50-pos. socket strips (bridged contacts). The cable is suitable for the SDV 531 card; cable length: 2.0 m

Cable - FLK 50-PA/EZ-DR/KS/ 300/YOC - 2314406



Assembled round cable with two molded 50-pos. socket strips (bridged contacts). The cable is suitable for the SDV 531 card; cable length: 3.0 m

Cable - FLK 50-PA/EZ-DR/KS/ 400/YOC - 2314419



Assembled round cable with two molded 50-pos. socket strips (bridged contacts). The cable is suitable for the SDV 531 card; cable length: 4.0 m

Cable - FLK 50-PA/EZ-DR/KS/ 600/YOC - 2314969



Assembled round cable with two molded 50-pos. socket strips (bridged contacts). The cable is suitable for SDV 531 card; cable length: 6.0 m.

Output module - UM-2KS50/ 8DO/RS/Z/C-L/SO225 - 2319485

Accessories

Cable - FLK 50-PA/EZ-DR/KS/ 800/YOC - 2314972



Assembled round cable with two molded 50-pos. socket strips (bridged contacts). The cable is suitable for SDV 531 card; cable length: 8.0 m.

Cable - FLK 50-PA/EZ-DR/KS/1000/YOC - 2314422



Assembled round cable with two molded 50-pos. socket strips (bridged contacts). The cable is suitable for the SDV 531 card; cable length: 10.0 m.

Cable - FLK 50-PA/EZ-DR/KS/1500/YOC - 2314435



Assembled round cable with two molded 50-pos. socket strips (bridged contacts). The cable is suitable for the SDV 531 card; cable length: 15.0 m.

Cable - FLK 50-PA/EZ-DR/KS/2000/YOC - 2314561



Assembled round cable with two molded 50-pos. socket strips (bridged contacts). The cable is suitable for the SDV 531 card; cable length: 20.0 m.

Cable - FLK 50-PA/EZ-DR/KS/2500/YOC - 2314574



Assembled round cable with two molded 50-pos. socket strips (bridged contacts). The cable is suitable for the SDV 531 card; cable length: 25.0 m.

Output module - UM-2KS50/ 8DO/RS/Z/C-L/SO225 - 2319485

Accessories

Cable - FLK 50-PA/EZ-DR/KS/3000/YOC - 2314587



Assembled round cable with two molded 50-pos. socket strips (bridged contacts). The cable is suitable for the SDV 531 card; cable length: 30.0 m

Cable - FLK 50-PA/EZ-DR/HF/KS/ 100/YOC - 2904985



Assembled halogen-free round cable with two molded 50-pos. socket strips (bridged contacts). The cable is suitable for the SDV 531 card; cable length: 1.0 m

Cable - FLK 50-PA/EZ-DR/HF/KS/ 200/YOC - 2904986



Assembled halogen-free round cable with two molded 50-pos. socket strips (bridged contacts). The cable is suitable for the SDV 531 card; cable length: 2.0 m

Cable - FLK 50-PA/EZ-DR/HF/KS/ 300/YOC - 2904987



Assembled halogen-free round cable with two molded 50-pos. socket strips (bridged contacts). The cable is suitable for the SDV 531 card; cable length: 3.0 m

Cable - FLK 50-PA/EZ-DR/HF/KS/ 400/YOC - 2904988



Assembled halogen-free round cable with two molded 50-pos. socket strips (bridged contacts). The cable is suitable for the SDV 531 card; cable length: 4.0 m

Output module - UM-2KS50/ 8DO/RS/Z/C-L/SO225 - 2319485

Accessories

Cable - FLK 50-PA/EZ-DR/HF/KS/ 500/YOC - 2904989



Assembled halogen-free round cable with two molded 50-pos. socket strips (bridged contacts). The cable is suitable for the SDV 531 card; cable length: 5.0 m

Cable - FLK 50-PA/EZ-DR/HF/KS/ 600/YOC - 2904990



Assembled halogen-free round cable with two molded 50-pos. socket strips (bridged contacts). The cable is suitable for the SDV 531 card; cable length: 6.0 m

Cable - FLK 50-PA/EZ-DR/HF/KS/ 700/YOC - 2904991



Assembled halogen-free round cable with two molded 50-pos. socket strips (bridged contacts). The cable is suitable for the SDV 531 card; cable length: 7.0 m

Cable - FLK 50-PA/EZ-DR/HF/KS/ 800/YOC - 2904992



Assembled halogen-free round cable with two molded 50-pos. socket strips (bridged contacts). The cable is suitable for the SDV 531 card; cable length: 8.0 m

Cable - FLK 50-PA/EZ-DR/HF/KS/ 900/YOC - 2904993



Assembled halogen-free round cable with two molded 50-pos. socket strips (bridged contacts). The cable is suitable for the SDV 531 card; cable length: 9.0 m

Output module - UM-2KS50/ 8DO/RS/Z/C-L/SO225 - 2319485

Accessories

Cable - FLK 50-PA/EZ-DR/HF/KS/1000/YOC - 2904994



Assembled halogen-free round cable with two molded 50-pos. socket strips (bridged contacts). The cable is suitable for the SDV 531 card; cable length: 10.0 m

Cable - FLK 50-PA/EZ-DR/HF/KS/1500/YOC - 2904995



Assembled halogen-free round cable with two molded 50-pos. socket strips (bridged contacts). The cable is suitable for the SDV 531 card; cable length: 15.0 m

Cable - FLK 50-PA/EZ-DR/HF/KS/2000/YOC - 2904996



Assembled halogen-free round cable with two molded 50-pos. socket strips (bridged contacts). The cable is suitable for the SDV 531 card; cable length: 20.0 m

Cable - FLK 50-PA/EZ-DR/HF/KS/2500/YOC - 2904997



Assembled halogen-free round cable with two molded 50-pos. socket strips (bridged contacts). The cable is suitable for the SDV 531 card; cable length: 25.0 m

Cable - FLK 50-PA/EZ-DR/HF/KS/3000/YOC - 2904998



Assembled halogen-free round cable with two molded 50-pos. socket strips (bridged contacts). The cable is suitable for the SDV 531 card; cable length: 30.0 m

Output module - UM-2KS50/ 8DO/RS/Z/C-L/SO225 - 2319485

Accessories

Cable - FLK 50-PA/EZ-DR/HF/KS/3500/YOC - 2904999



Assembled halogen-free round cable with two molded 50-pos. socket strips (bridged contacts). The cable is suitable for the SDV 531 card; cable length: 35.0 m

Cable - FLK 50-PA/EZ-DR/HF/KS/4000/YOC - 2905000



Assembled halogen-free round cable with two molded 50-pos. socket strips (bridged contacts). The cable is suitable for the SDV 531 card; cable length: 40.0 m

Cable - FLK 50-PA/EZ-DR/HF/KS/4500/YOC - 2905001



Assembled halogen-free round cable with two molded 50-pos. socket strips (bridged contacts). The cable is suitable for the SDV 531 card; cable length: 45.0 m

Cable - FLK 50-PA/EZ-DR/HF/KS/5000/YOC - 2905002



Assembled halogen-free round cable with two molded 50-pos. socket strips (bridged contacts). The cable is suitable for the SDV 531 card; cable length: 50.0 m
