

Fiber optic coupling - FL MM PATCH COUPLER LC-LC - 2700312


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Coupling, LC/LC, can be used for multi-mode glass fibers



Key Commercial Data

Packing unit	1 STK
GTIN	 4 046356 542715
GTIN	4046356542715
Weight per Piece (excluding packing)	20.000 g
Custom tariff number	85367000
Country of origin	Germany

Technical data

Mechanical characteristics

Number of positions	2
Number of slots	1
Connection profile	LC-Duplex
Fiber type	Multi-mode fiberglass
Fiber	50/125 µm and 62.5/125 µm
Ferrule diameter	1.25 mm
Number of fibers	2
Insertion/withdrawal cycles	≥ 500
Connection method	Coupling
Color	beige
Degree of protection	IP20

Fiber optic coupling - FL MM PATCH COUPLER LC-LC - 2700312

Technical data

Ambient conditions

Ambient temperature (operation)	-25 °C ... 70 °C
Degree of protection	IP20

Material data

Flammability rating according to UL 94	V0
Housing material	PBT
Ferrule material	Zirconia ceramics
Ferrule holder color	white

Standards and Regulations

Flammability rating according to UL 94	V0
--	----

Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"