

## Power storage devices - UPS-BAT/VRLA/ 24DC/ 1.3AH - 2320296

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Power storage device, lead AGM, VRLA technology, 24 V DC, 1.3 Ah, tool-free battery replacement, automatic detection, and communication with QUINT UPS-IQ

### Why buy this product

- Tool-free battery replacement
- Communication with QUINT UPS IQ

### Key commercial data

Packing unit	0
Minimum order quantity	1
Catalog page	Page 618 (IF-2011)
GTIN	 4 046356 554176
Custom tariff number	85072080
Country of origin	CHINA

### Technical data

#### Input data

Nominal input voltage	24 V DC
Buffer period	20 min (2 A)
Buffer period	5 min (5 A)

#### Output data

Output current	max. 15 A
Connection in parallel	15
Connection in series	No
Output fuse	1x 15 A

#### General data

IQ technology	Yes
Disposal	Used batteries must not be thrown away with household waste, they should instead be disposed of in accordance with applicable national regulations. They can also be returned to Phoenix Contact or the manufacturer.
Width	54 mm

# Power storage devices - UPS-BAT/MRLA/ 24DC/ 1.3AH - 2320296

## Technical data

### General data

Height	157 mm
Depth	113 mm
Net weight	1.7 kg
Memory medium	1.3 Ah battery
Degree of protection	IP20
Protection class	III
Ambient temperature (operation)	0 °C ... 40 °C
Ambient temperature (storage/transport)	0 °C ... 40 °C
Max. permissible relative humidity (operation)	95 %
Mounting position	horizontal DIN rail NS 35, EN 60715
Standard - Electrical safety	EN 60950-1/VDE 0805 (SELV)
Standard - Electrical safety	EN 61558-2-17
Standard – Electronic equipment for use in electrical power installations and their assembly into electrical power installations	EN 50178/VDE 0160 (PELV)
UL approvals	UL/C-UL listed UL 508
UL approvals	UL/C-UL Recognized UL 60950
UL approvals	UL/C-UL Recognized UL 1778
VdS approval	G 196049

## Classifications

### eclass

eCl@ss 4.1	27040603
eCl@ss 5.0	27040603
eCl@ss 5.1	27040603
eCl@ss 6.0	27040603
eCl@ss 7.0	27040603

### etim

ETIM 4.0	EC000382
----------	----------

### unspsc

UNSPSC 6.01	30211510
UNSPSC 7.0901	39121011
UNSPSC 11	39121011
UNSPSC 12.01	39121011
UNSPSC 13.2	39121011

## Approvals

### Approvals

# Power storage devices - UPS-BAT/VRLA/ 24DC/ 1.3AH - 2320296

## Approvals

Approvals

UL Recognized / UL Listed / cUL Recognized / cUL Listed / UL Recognized / cULus Recognized / cUL Listed

---

Ex Approvals

---

Approvals submitted

---

## Approval details

UL Recognized

UL Listed

cUL Recognized

cUL Listed

UL Recognized

cULus Recognized

cUL Listed

## Accessories

Accessories

## Power storage devices - UPS-BAT/VRLA/ 24DC/ 1.3AH - 2320296

### Accessories

Electronic housing - UTA 107 - 2853983

Universal DIN rail adapter, for screwing on switchgear



---

### Drawings

# Power storage devices - UPS-BAT/VRLA/ 24DC/ 1.3AH - 2320296

Block diagram



