

3M

Masking Tape

2307

Technical Data

December, 2007

Product Description 3M™ Masking Tape 2307 is a general purpose masking tape for holding, bundling, sealing, general paint masking and a vast number of other jobs where a pressure-sensitive tape is needed.

Product Construction	Backing	Adhesive	Standard Roll Length
	Natural colored crepe paper	Rubber	(55 m) 60 yds.

Typical Physical Properties		ASTM Test Method
Adhesion to Steel:	28 oz./in. width (31 N/100 mm)	D-3330
Tensile Strength:	23 lbs./in. width (403 N/100 mm)	D-3759
Elongation at Break:	8%	D-3759
Tape Thickness:	5.2 mils (0.13 mm)	D-3652
Temperature Use Range:	Up to 200°F (93°C) for 30 min.	

- Features**
- Tape has been tested and found to meet the requirements of ASTM D 6123 / D 6123M-97. 3M does not test each lot for compliance to this specification.
 - Rubber adhesive for instant adhesion that sticks easily and helps reduce labor.
 - Good holding power to help resist lifting or curling.
 - Crepe paper backing that is conformable to maintain integrity when formed around a corner.
 - Easy tear and sliver resistant
 - Good paint hold-out that resists bleed-through.
 - Controlled unwind.
 - Tape may become very difficult to remove if subjected to prolonged outdoor exposure.

3M™ Masking Tape

2307

Storage Store under normal conditions of 70°F (21°C) and 50% R.H. in the original carton.

Shelf Life To obtain best performance, use this product within one year from date of manufacture.

Product Use All statements, technical information and recommendations contained in this document are based upon tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method of application.

Warranty and Limited Remedy Unless stated otherwise in 3M's product literature, packaging inserts or product packaging for individual products, 3M warrants that each 3M product meets the applicable specifications at the time 3M ships the product. Individual products may have additional or different warranties as stated on product literature, package inserts or product packages. 3M MAKES NO OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's application. If the 3M product is defective within the warranty period, your exclusive remedy and 3M's and seller's sole obligation will be, at 3M's option, to replace the product or refund the purchase price.

Limitation of Liability Except where prohibited by law, 3M and seller will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

ISO 9001:2000

This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001:2000 standards.



Industrial Adhesives and Tapes Division

3M Center, Building 21-1W-10, 900 Bush Avenue
St. Paul, MN 55144-1000
800-362-3550 • 877-369-2923 (fax)
www.3M.com/industrial



Recycled Paper
40% pre-consumer
10% post-consumer

3M is a trademark of 3M Company.
Printed in U.S.A.
©3M 2007 70-0709-4543-4 (12/07)

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[3M:](#)

[2307-12mmx55m](#) [2307-18mmx55m](#) [2307-24mmx55m](#) [2307-36mmx55m](#) [2307-48mmx55m](#) [2307-72mmx55m](#) [2307-96mmx55m](#)