

# CABLE-D- 9SUB/F/OE/0,25/S/6,0M


Order No.: 2926072

The figure shows the 25-pos. version



<http://catalog.phoenixcontact.net/phoenix/treeViewClick.do?UID=2926072>

Shielded cable with a 9-pos. D-SUB female connector and one open end. The individual wires are labeled 1 to 9 and fitted with ferrules. The braided shield is routed to a separate cable end. Cable length: 6 m.

Commercial data	
EAN	 4 046356 547765
Note	Made-to-order
sales group	I682
Pack	1 Pcs.
Customs tariff	85444290
Gross weight in pieces	0.43 KG
Net weight per piece	0.4404 KG
Catalog page information	Page 516 (C-7-2013)

#### Product notes

WEEE/RoHS-compliant since:  
02/09/2010



<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data	
<b>General</b>	
Nominal voltage $U_N$	125 V AC/DC
Max. current carrying capacity per path	2 A
Max. conductor resistance	$\leq 0.09 \Omega/m$
Length of cable	6 m
Single wire, cross section	0.25 mm <sup>2</sup>
AWG	24

External diameter	7.5 mm
Shielding	yes
	Tinned copper-braided shield, approx. 85% covering
Insertion/withdrawal cycles	> 200

#### Environmental conditions

Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C
Flame resistance	IEC 60332-1

#### Connector, module side

Number of positions	9
Connectors	D-SUB socket strip
Number of plugs	1

#### Connector, controller side

Number of positions	9
Connectors	Open end
Number of plugs	0

#### Certificates / Approvals



Certification cULus Recognized

Certifications applied for:

Certification Ex:

---

**Address**

PHOENIX CONTACT Deutschland GmbH  
Flachmarktstr. 8  
32825 Blomberg, Germany  
Phone +49 5235 3 12000  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>



© 2014 Phoenix Contact  
Technical modifications reserved;