


FLKM14/FLK14/ZFKDS/DO8/SO200

Order No.: 2310853

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2310853>

VARIOFACE interface module for redundant connection of 2x8 output channels (SIMATIC® S7 / S5) via 2xFLK14 on spring-cage terminal blocks, signals are decoupled by diodes

Commercial data

| | |
|----------------|--|
| GTIN (EAN) |  4 046356 128537 |
| Note | Made-to-order |
| sales group | I009 |
| Pack | 1 pcs. |
| Customs tariff | 85369010 |

Product notesWEEE/RoHS-compliant since:
09/19/2008

<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data**General data**

| | |
|---|------------------|
| Nominal voltage U_N | 24 V DC |
| Max. current carrying capacity per branch | 1 A |
| Width | 57 mm |
| Height | 87000 mm |
| Depth | 62 mm |
| Status display | No |
| Ambient temperature (operation) | -20 °C ... 50 °C |
| Ambient temperature (storage/transport) | -20 °C ... 70 °C |

| | |
|------------------------|---------------------------|
| Test voltage | 500 V AC |
| Mounting position | Any |
| Assembly instructions | In rows with zero spacing |
| Standards/regulations | DIN EN 50178 |
| Pollution degree | 2 |
| Surge voltage category | II |

Connection data

| | |
|--|--|
| Connection 1 | PCB connection |
| Connection method | Spring-cage connection |
| Conductor cross section solid min. | 0.2 mm ² |
| Conductor cross section solid max. | 2.5 mm ² |
| Conductor cross section stranded min. | 0.2 mm ² |
| Conductor cross section stranded max. | 1.5 mm ² |
| Conductor cross section AWG/kcmil min. | 24 |
| Conductor cross section AWG/kcmil max | 14 |
| Stripping length | 7 mm |
| Connection 2 | Flat-ribbon cable connection |
| Number of connections | 2 |
| Connection method | Flat-ribbon cable plug connector in acc. with IEC 60603-13 |
| Number of positions | 14 |

Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2011 Phoenix Contact
Technical modifications reserved;