

Cable - CABLE-D- 9SUB/M/OE/0,25/S/4,0M - 2926412

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Assembled shielded round cable; Connection 1: Single wires (9-position) (The wires are marked and fitted with ferrules. The braided shield is routed to a separate cable end.); Connection 2: D-SUB pin strip (1x 9-position); Cable length: 4 m




The figure shows the 25-pos. version

Why buy this product

- ✓ Individual wire marking: 1, 2, 3, 4, etc.
- ✓ Individual wires fitted with ferrules
- ✓ Connector according to IEC 60807-2/DIN 41652
- ✓ D-SUB socket or pin strip at one end
- ✓ Screw connection: 2 UNC 4-40 screws
- ✓ Open end at one end
- ✓ 1:1 connection
- ✓ Shield connection: H05V-K 1 mm² cable, black, 0.5 m in length

RoHS

Key Commercial Data

Packing unit	1 STK
GTIN	 4 046356 548151
GTIN	4046356548151
Weight per Piece (excluding packing)	300.000 g
Custom tariff number	85444290
Country of origin	Germany

Technical data

General

Nominal voltage U _N	25 V AC
--------------------------------	---------

Cable - CABLE-D- 9SUB/M/OE/0,25/S/4,0M - 2926412

Technical data

General

	60 V DC
Max. current carrying capacity per path	2 A
Max. conductor resistance	$\leq 0.09 \Omega/\text{m}$
Length of cable	4 m
Single wire, cross section	0.25 mm ²
Single wire, cross section [AWG]	24
External diameter	7.5 mm
Shielding	yes
	Tinned copper-braided shield, approx. 85% covering
Insertion/withdrawal cycles	> 200

Environmental conditions

Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C
Flame resistance	IEC 60332-1
	DIN VDE 0482 Part 332-1

Connector 1

Connection name	Field level
Connection method	D-SUB pin strip
Number of connections	1
Number of positions	9

Connector 2

Connection name	Controller level
Connection method	Single wires
Number of positions	9
Note	The wires are marked and fitted with ferrules. The braided shield is routed to a separate cable end.

Supported controller

Controller	universal
------------	-----------

Standards and Regulations

Connection in acc. with standard	CUL
Flame resistance	IEC 60332-1
	DIN VDE 0482 Part 332-1

Color code

Connector 1 = connector 2 (optional) = wire color	D-SUB 9 (1) = white
	D-SUB 9 (2) = brown

Cable - CABLE-D- 9SUB/M/OE/0,25/S/4,0M - 2926412

Technical data

Color code

	D-SUB 9 (3) = green
	D-SUB 9 (4) = yellow
	D-SUB 9 (5) = gray
	D-SUB15 (6) = pink
	D-SUB 9 (7) = blue
	D-SUB 9 (8) = red
	D-SUB 9 (9) = black

Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss

eCl@ss 5.1	27249205
eCl@ss 6.0	27249205
eCl@ss 7.0	27249205
eCl@ss 8.0	27249205
eCl@ss 9.0	27242220

ETIM

ETIM 2.0	EC000237
ETIM 3.0	EC000237
ETIM 4.0	EC000237
ETIM 5.0	EC000237
ETIM 6.0	EC000237

UNSPSC

UNSPSC 6.01	26121620
UNSPSC 7.0901	26121620
UNSPSC 11	26121620
UNSPSC 12.01	26121620
UNSPSC 13.2	26121620

Approvals

Approvals

Cable - CABLE-D- 9SUB/M/OE/0,25/S/4,0M - 2926412


Approvals


Approvals


UL Recognized / cUL Recognized / CSA / EAC / cULus Recognized

Ex Approvals

Approval details

UL Recognized			http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	FILE E 238705
Nominal current I _N		2 A		
Nominal voltage U _N		125 V		

cUL Recognized			http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	FILE E 238705
Nominal current I _N		2 A		
Nominal voltage U _N		125 V		

CSA		http://www.csagroup.org/services/testing-and-certification/certified-product-listing/	70002966
Nominal current I _N	1 A		
Nominal voltage U _N	125 V		

EAC		RU C- DE.A*30.B00767	
-----	---	-------------------------	--

cULus Recognized		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm
------------------	---	---

Cable - CABLE-D- 9SUB/M/OE/0,25/S/4,0M - 2926412

Accessories

Accessories

Marker carrier cable

Cable marker carrier - KME - 0807083



Cable marker carrier, white, unlabeled, Mounting type: Assembly with cable binders, Cable diameter: >5 mm, Lettering field: 20 mm x 8 mm