

Single relay - REL-SW120/B104 - 2960397

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



KAMMRELAIS ®, contact B 104, size 1, low-level contact, 2 PDTs, input voltage 120 V AC

The illustration shows the version
REL-SG 12-24/B 104

RoHS

Key Commercial Data

Packing unit	1 STK
GTIN	 4 017918 086794
GTIN	4017918086794
Weight per Piece (excluding packing)	42.450 g
Custom tariff number	85364900
Country of origin	Germany

Technical data

Ambient conditions

Ambient temperature (operation)	-40 °C ... 70 °C
Ambient temperature (storage/transport)	-40 °C ... 70 °C

Coil side

Nominal input voltage U_N	120 V AC
Input voltage range in reference to U_N	0.8 ... 1.1
Typical response time	4 ms ... 15 ms
Typical release time range	4 ms ... 15 ms
Coil resistance	3500 Ω $\pm$ 10 %

Contact side

Single relay - REL-SW120/B104 - 2960397

Technical data

Contact side

Contact type	2 PDT
Type of switch contact	Single contact
Contact material	Ag, gold-flashed
Maximum switching voltage	125 V AC
	150 V DC
Maximum inrush current	2 A
Limiting continuous current	2 A
Interrupting rating (ohmic load) max.	48 W (at 24 V DC)
	40 W (at 48 V DC)
	40 W (at 60 V DC)
	45 W (at 110 V DC)
	50 VA (for 125 V AC)

General

Test voltage relay winding/relay contact	500 V AC (50 Hz, 1 min.)
Test voltage PDT/PDT	500 V AC (50 Hz, 1 min.)
Mechanical service life	Approx. 10 ⁷ cycles

Classifications

eCl@ss

eCl@ss 4.0	27371104
eCl@ss 4.1	27371104
eCl@ss 5.0	27371601
eCl@ss 5.1	27371601
eCl@ss 6.0	27371601
eCl@ss 7.0	27371601
eCl@ss 8.0	27371601
eCl@ss 9.0	27371601

ETIM

ETIM 2.0	EC001437
ETIM 3.0	EC001437
ETIM 4.0	EC001437
ETIM 5.0	EC001437

UNSPSC

UNSPSC 6.01	30211916
-------------	----------

Single relay - REL-SW120/B104 - 2960397

Classifications

UNSPSC

UNSPSC 7.0901	39121515
UNSPSC 11	39121515
UNSPSC 12.01	39121515
UNSPSC 13.2	39121515