


TT-UKK5-M/ 60DC

Order No.: 2795986

The illustration shows version TT-UKK5-M-24 DC



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2795986>

Double-level modular terminal block with suppressor diode as surge protection between both levels, disconnect knife in the upper level, nominal voltage: 60 V DC, for mounting on NS 32 or NS 35/7.5, closed housing, terminal width: 6.2 mm, terminal height: 68 mm

Commercial data

GTIN (EAN)	4017918073244
sales group	J303
Pack	50 pcs.
Customs tariff	85363010
Weight/Piece	0.02607 KG
Catalog page information	Page 88 (TT-2007)

Product notes

WEEE/RoHS-compliant since:
05/21/2007



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

General

Housing material	PA
Inflammability class acc. to UL 94	V2
Color	black

Standards for air and creepage distances	VDE 0110-1
Total surge current (8/20) μ s	69 A
Ambient temperature (operation)	-40 °C ... 85 °C
Mounting type	DIN rail/G-profile rail
Design	Double-level terminal block with disconnect knife
Number of positions	1
Degree of protection	IP20
Direction of action	Line-Line
Width	6.20 mm
Height	68.00 mm
Length	80.00 mm

Protective circuit

IEC category	C3
VDE requirement class	C3
Nominal voltage U_N	60 V DC
Max. operating voltage U_{max}	70 V DC
Arrester rated voltage U_C	70 V DC
	49 V AC
Arrester rated voltage U_C (Core-Core)	70 V DC
Arrester rated voltage U_C (Core-Earth)	49 V AC
Nominal current I_N	12 A (45°C)
Operating effective current I_C at U_C	$\leq 5 \mu$ A
Nominal discharge surge current I_n (8/20) μ s (Core-Core)	69 A
Total surge current (8/20) μ s	69 A
Max. discharge surge current I_{max} (8/20) μ s maximum (Core-Core)	69 A
Nominal pulse current I_{an} (10/1000) μ s (Core-Core)	13.3 A
Output voltage limitation at 1 kV/ μ s (Core-Core) static	≤ 100 V
Residual voltage at I_n , (conductor-conductor)	≤ 120 V
Response time t_A (Core-Core)	≤ 1 ns
Cut-off frequency f_g (3 dB), sym. in 150 Ohm system	Typ. 3.2 MHz
Capacity (Core-Core)	≤ 0.65 nF

Surge carrying capacity in acc. with IEC 61643-21 (Core-Core)	C3 (10 A)
---	-----------

Connection data

Type of connection	Screw connection
Connection type IN	Screw terminal blocks
Connection type OUT	Screw terminal blocks
Screw thread	M3
Tightening torque	0.5 Nm
Stripping length	8 mm
Conductor cross section stranded min.	0.2 mm ²
Conductor cross section stranded max.	4 mm ²
Conductor cross section solid min.	0.2 mm ²
Conductor cross section solid max.	4 mm ²
Conductor cross section AWG/kcmil min.	24
Conductor cross section AWG/kcmil max	12

Connection, protective circuit

Standards/regulations	IEC 61643-21
-----------------------	--------------

Certificates / Approvals




Certification CSA, GOST

CSA


Nominal voltage U _N	60 V
Nominal current I _N	12 A
AWG/kcmil	24-12

Diagrams/Drawings

Circuit diagram



Schematic diagram



Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2010 Phoenix Contact
Technical modifications reserved;