

Interface module - VIP-3/SC/D37SUB/M/HW/C300 - 2900675

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



VARIOFACE module, with screw connection and male D-Subminiature pin strip, for mounting on NS 35 rails, 37-pos.



Key commercial data

Packing unit	1 pc
GTIN	 4 046356 535564
Weight per Piece (excluding packing)	212.7 g
Custom tariff number	85369010
Country of origin	United States
Note	Made to Order (non-returnable)

Technical data

Dimensions

Width	88 mm
Height	69 mm
Depth	62 mm

Ambient conditions

Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C

General

Max. permissible operating voltage	24 V DC
Max. perm. current (per branch)	2 A
Number of positions	37
Status display	No
Mounting position	any
Assembly instructions	In rows with zero spacing

Interface module - VIP-3/SC/D37SUB/M/HW/C300 - 2900675

Technical data

General

Standards/regulations	DIN EN 50178
-----------------------	--------------

Connection data for connection 1

Connection name	PCB connection
Connection in acc. with standard	IEC / EN
Connection method	Screw connection
Conductor cross section solid min.	0.2 mm ²
Conductor cross section solid max.	4 mm ²
Conductor cross section stranded min.	0.2 mm ²
Conductor cross section stranded max.	2.5 mm ²
Conductor cross section AWG/kcmil min.	24
Conductor cross section AWG/kcmil max	12
Stripping length	8 mm
Screw thread	M 3

Connection data for connection 2

Connection name	D-SUB connection
Number of connections	1
Connection method	D-SUB pin strip
Number of positions	37

Supported controller

Controller	HONEYWELL C300
- suitable I/O card	TAIX01 (non-redundant)
	TAIX11 (redundant)

Classifications

eCl@ss

eCl@ss 4.0	27250313
eCl@ss 4.1	27250313
eCl@ss 5.0	27250313
eCl@ss 5.1	27250313
eCl@ss 6.0	27242608
eCl@ss 7.0	27141152
eCl@ss 8.0	27141152

ETIM

ETIM 2.0	EC001434
ETIM 3.0	EC001604
ETIM 4.0	EC001604
ETIM 5.0	EC002780

Interface module - VIP-3/SC/D37SUB/M/HW/C300 - 2900675

Classifications

UNSPSC

UNSPSC 6.01	30211824
UNSPSC 7.0901	39121421
UNSPSC 11	39121421
UNSPSC 12.01	39121421
UNSPSC 13.2	39121421

Approvals

Approvals

Approvals

UL Recognized / cUL Recognized / EAC / cULus Recognized

Ex Approvals

Approvals submitted

Approval details

UL Recognized 	
mm²/AWG/kcmil	30-12
Nominal current I _N	2 A
Nominal voltage U _N	125 V

cUL Recognized 	
mm²/AWG/kcmil	30-12
Nominal current I _N	2 A
Nominal voltage U _N	125 V

EAC

Interface module - VIP-3/SC/D37SUB/M/HW/C300 - 2900675

Approvals

cULus Recognized 

Accessories

Accessories

System cable

Cable - CABLE-D37SUB/B/B/ 100/KONFEK/S - 2305509



Assembled, shielded circular cable, with D-SUB socket strip, 37-pos. from both sides, cable length: 1 m

Cable - CABLE-D37SUB/B/B/ 200/KONFEK/S - 2305512



Assembled, shielded circular cable, with D-SUB socket strip, 37-pos. from both sides, cable length: 2m

Cable - CABLE-D37SUB/B/B/ 300/KONFEK/S - 2305525



Assembled, shielded circular cable, with D-SUB socket strip, 37-pos. from both sides, cable length: 3 m

Cable - CABLE-D37SUB/B/B/ 400/KONFEK/S - 2900759



Assembled, shielded round cable, with 37-pos. D-SUB socket strip on both sides; cable length 4 m

Interface module - VIP-3/SC/D37SUB/M/HW/C300 - 2900675

Accessories

Cable - CABLE-D37SUB/B/B/ 600/KONFEK/S - 2900760



Assembled, shielded round cable, with 37-pos. D-SUB socket strip on both sides; cable length 6 m

Cable - CABLE-D37SUB/B/B/ 800/KONFEK/S - 2900761



Assembled, shielded round cable, with 37-pos. D-SUB socket strip on both sides; cable length 8 m

Cable - CABLE-D37SUB/B/B/1000/KONFEK/S - 2900762



Assembled, shielded round cable, with 37-pos. D-SUB socket strip on both sides; cable length 10 m

Cable - CABLE-D37SUB/B/B/1500/KONFEK/S - 2900763



Assembled, shielded round cable, with 37-pos. D-SUB socket strip on both sides; cable length 15 m

Cable - CABLE-D37SUB/B/B/2000/KONFEK/S - 2900764



Assembled, shielded round cable, with 37-pos. D-SUB socket strip on both sides; cable length 20 m

Necessary add-on products

