

Interface module - UM-D37M/DS/FU/LED/DG/C300/R - 2905133

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

VARIOFACE module intended for use with Honeywell Experion C300 16-channel digital cards:




Why buy this product

- ✓ These VARIOFACE modules are used in combination with the relevant front adapters
- ✓ Per channel pluggable 1 A fusing
- ✓ UM-PRO housing
- ✓ Designed to be mounted on the right side of the cabinet
- ✓ DIN rail mounting
- ✓ LED blown fusing indication
- ✓ Per channel disconnects with test points



Key Commercial Data

Packing unit	1 STK
GTIN	 4 046356 959049
GTIN	4046356959049
Weight per Piece (excluding packing)	400.000 g
Custom tariff number	85369010
Country of origin	United States

Technical data

Dimensions

Width	124 mm
Height	142.3 mm
Depth	65.6 mm

Interface module - UM-D37M/DS/FU/LED/DG/C300/R - 2905133

Technical data

Ambient conditions

Ambient temperature (operation)	-40 °C ... 60 °C
Ambient temperature (storage/transport)	-40 °C ... 75 °C

General

Max. perm. operating voltage	24 V DC
Max. perm. current (per branch)	1 A (fuse limited)
Number of positions	37
Status display	No
Mounting position	any
Assembly instructions	In rows with zero spacing

Connection data for connection 1

Connection name	Field level
Connection method	Screw connection with disconnect knife
Stripping length	8 mm
Screw thread	M 3
Conductor cross section solid	0.2 mm ² ... 4 mm ²
Conductor cross section flexible	0.2 mm ² ... 2.5 mm ²
Conductor cross section AWG	24 ... 12

Connection data for connection 2

Connection name	Controller level
Connection method	D-SUB pin strip
Number of connections	1
Number of positions	37

Supported controller

Controller	HONEYWELL Experion PKS C300/C-Series
- suitable I/O card	TDIL01 (non-redundant)
	TDIL11 (redundant)
	TDIL51 (non-redundant)
	TDIL61 (redundant)
	TDOB01 (non-redundant)
	TDOB11 (redundant)
	TDOB51 (non-redundant)
	TDOB61 (redundant)
Controller	Honeywell Experion LX Series 8
- suitable I/O card	8X-TDILA1
	8X-TDILB1


Interface module - UM-D37M/DS/FU/LED/DG/C300/R - 2905133

Technical data

Standards and Regulations

Standards/regulations	DIN EN 50178
-----------------------	--------------

Drawings



dimensional drawing of left hand version

Classifications

eCl@ss

eCl@ss 4.0	27250313
eCl@ss 4.1	27250313
eCl@ss 5.0	27250313
eCl@ss 5.1	27250313
eCl@ss 7.0	27141152
eCl@ss 8.0	27141152
eCl@ss 9.0	27141152

ETIM

ETIM 4.0	EC002780
ETIM 5.0	EC002780
ETIM 6.0	EC002780

UNSPSC

UNSPSC 13.2	39121432
-------------	----------

Approvals

Approvals

Interface module - UM-D37M/DS/FU/LED/DG/C300/R - 2905133

Approvals

Approvals

UL Recognized / cUL Recognized / EAC / cULus Recognized

Ex Approvals

Approval details

UL Recognized		http://database.ul.com/cgi-bin/XYVV/template/LISEXT/1FRAME/index.htm	FILE E 238705
---------------	--	---	---------------

cUL Recognized		http://database.ul.com/cgi-bin/XYVV/template/LISEXT/1FRAME/index.htm	FILE E 238705
----------------	--	---	---------------

EAC			RU C- DE.A*30.B.01742
-----	--	--	--------------------------

cULus Recognized		http://database.ul.com/cgi-bin/XYVV/template/LISEXT/1FRAME/index.htm	
------------------	--	---	--

Accessories

Accessories

System cable

Cable - CABLE-D37SUB/B/B/ 100/KONFEK/S - 2305509



Assembled shielded round cable; Connection 1: D-SUB socket strip (1x 37-position); Connection 2: D-SUB socket strip (1x 37-position); Cable length: 1 m

Interface module - UM-D37M/DS/FU/LED/DG/C300/R - 2905133

Accessories

Cable - CABLE-D37SUB/B/B/ 200/KONFEK/S - 2305512



Assembled shielded round cable; Connection 1: D-SUB socket strip (1x 37-position); Connection 2: D-SUB socket strip (1x 37-position); Cable length: 2 m

Cable - CABLE-D37SUB/B/B/ 300/KONFEK/S - 2305525



Assembled shielded round cable; Connection 1: D-SUB socket strip (1x 37-position); Connection 2: D-SUB socket strip (1x 37-position); Cable length: 3 m

Cable - CABLE-D37SUB/B/B/ 400/KONFEK/S - 2900759



Assembled shielded round cable; Connection 1: D-SUB socket strip (1x 37-position); Connection 2: D-SUB socket strip (1x 37-position); Cable length: 4 m

Cable - CABLE-D37SUB/B/B/ 600/KONFEK/S - 2900760



Assembled shielded round cable; Connection 1: D-SUB socket strip (1x 37-position); Connection 2: D-SUB socket strip (1x 37-position); Cable length: 6 m

Cable - CABLE-D37SUB/B/B/ 800/KONFEK/S - 2900761



Assembled shielded round cable; Connection 1: D-SUB socket strip (1x 37-position); Connection 2: D-SUB socket strip (1x 37-position); Cable length: 8 m

Interface module - UM-D37M/DS/FU/LED/DG/C300/R - 2905133

Accessories

Cable - CABLE-D37SUB/B/B/1000/KONFEK/S - 2900762



Assembled shielded round cable; Connection 1: D-SUB socket strip (1x 37-position); Connection 2: D-SUB socket strip (1x 37-position); Cable length: 10 m

Cable - CABLE-D37SUB/B/B/1500/KONFEK/S - 2900763



Assembled shielded round cable; Connection 1: D-SUB socket strip (1x 37-position); Connection 2: D-SUB socket strip (1x 37-position); Cable length: 15 m

Cable - CABLE-D37SUB/B/B/2000/KONFEK/S - 2900764



Assembled shielded round cable; Connection 1: D-SUB socket strip (1x 37-position); Connection 2: D-SUB socket strip (1x 37-position); Cable length: 20 m

Necessary add-on products

Front adapters - FLKM-PA-D37/HW/DIO/C300 - 2901423



VARIOFACE front adapter, for Honeywell C300, Series C I/O, maximum of 1 x 16 channels can be connected (37-pos. D-SUB connector). Specifically for connecting digital, redundant I/O cards.

Spare parts

Fuse set - FUSE/TE5/1A/F-10PCS - 2905277



Plug-in fuse (TE5[®]); nominal current: 1 A; tripping behavior: fast-blow (F)

Interface module - UM-D37M/DS/FU/LED/DG/C300/R - 2905133

Accessories

Phoenix Contact 2017 © - all rights reserved
<http://www.phoenixcontact.com>