


U.I. Lapp GmbH	PRODUCT INFORMATION	
	LiY	07.11.2014

Stranded hook-up wire for telecommunication devices and electronic components



Info

PVC control hook-up wire
Favourable

Application range

Stranded hook-up wires for wiring of telecommunication devices and electronic components within devices

Product Make-up

Stranded copper wire
Core insulation: PVC-based YI 2/TI 2 acc. VDE 0207-4

Norm references / Approvals

Based on VDE 0812

Product features

Flame-retardant according IEC 60332-1-2
Spool: d1 = 18 mm; d2 = 150 mm; b = 85 mm

Remark

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request. Copper price basis: EUR 150/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges. Photographs are not to scale and do not represent detailed images of the respective products.

Technical Data

Peak operating voltage:	500 V (0.14 mm ²) 900 V (0.25 sq.mm)
Classification:	ETIM 5.0 Class-ID: EC000993 ETIM 5.0 Class-Description: Single core cable
Conductor stranding:	0.14 mm ² : ≥ 18 strands (each with 0.10 mm Ø) 0.25 mm ² : ≥ 14 strands (each with 0.15 mm Ø)
Nominal voltage:	Operating voltage < 50 VAC UPP - peak-to-peak voltage: ≤ 250 V
Test voltage:	1200 V (0.14 mm ²) 2500 V (0.25 mm ²)
Temperature range:	Fixed installation: -30 °C to +70 °C


Product Management	Document: LAPP_PRO167EN.pdf	1 / 3
--------------------	-----------------------------	-------





LIV

07.11.2014

Part number	Conductor cross-section (mm ²)	Outer diameter (mm)	Core colour	m/spool	Copper index (kg/km)
4125001S	0,14	1.1	black	500	1.35
4125002S	0,14	1.1	blue	500	1.35
4125003S	0,14	1.1	brown	500	1.35
4125005S	0,14	1.1	yellow	500	1.35
4125006S	0,14	1.1	green	500	1.35
4125007S	0,14	1.1	violet	500	1.35
4125009S	0,14	1.1	orange	500	1.35
4125104S	0,14	1.1	red	500	1.35
4125105S	0,14	1.1	white	500	1.35
4125106S	0,14	1.1	grey	500	1.35
4126000S	0,25	1.3	green/yellow	250	2.4
4126001S	0,25	1.3	black	250	2.4
4126002S	0,25	1.3	blue	250	2.4
4126014S	0,25	1.3	Dark blue	250	2.4
4126003S	0,25	1.3	brown	250	2.4
4126005S	0,25	1.3	yellow	250	2.4
4126006S	0,25	1.3	green	250	2.4
4126007S	0,25	1.3	violet	250	2.4
4126008S	0,25	1.3	pink	250	2.4
4126009S	0,25	1.3	orange	250	2.4
4126104S	0,25	1.3	red	250	2.4
4126105S	0,25	1.3	white	250	2.4
4126106S	0,25	1.3	grey	250	2.4

U.I. Lapp GmbH	PRODUCT INFORMATION	
	LiY	07.11.2014



Product Management	Document: LAPP_PRO167EN.pdf	3 / 3
--------------------	-----------------------------	-------