




PART NO.


2MJ-0401A110


REVISIONS								
ECN#	REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE
-	1.1	RELEASED	AB	14/02/14	ER	14/02/14	ER	14/02/14













FARTH SHIFLD

PLUG

A-A' SECTION OF EARTH SHIELD

Dimensions: Millimetres

0.60 + 3.18

5.00 PCB LAYOUT

(SOLDER SIDE)

TOLERANCE: ±0.05

Important Notice: This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell plc 2012.

ø1.10 +0.00

6.00

TOLERANCES:

UNLESS OTHERWISE SPECIFIED, **DIMENSIONS ARE** FOR REFERENCE PURPOSES ONLY.

	DRAWN BY:	DATE:		
	AB	14/02/14		
	CHECKED BY:	DATE:		
	ER	14/02/14		
	APPROVED BY:	DATE:		
	ER	14/02/14		

Specifications:

Gender : Socket : 7.5A **Current Rating** Connector Mounting : PCB : PCB **Contact Termination** Colour : Black Connector Body Material : Metal Connector Type : Circular **Contact Material** : Brass Contact Plating : Tin Insulation Resistance : 50mΩ

: PCB Through Hole Mounting Type

No. of Contacts

Solder Heat Resistance : Wave Soldering 260°C 10 secs.

For Wave Soldering Lead-Free Process

No	Description	Qty	Material	Plating & Colour	
Α	Body	1	PBT+15% GF	Black Colour	
В	Cover	1	PBT+15% GF	Black Colour	
С	Earth Shield	1	C2680-H, T = 0.4mm	Nickel Plating	
D	Contact Terminal	2	C5191-H, T = 0.3mm	Silver Plating	
Е	Contact Terminal	1	C5191-H, 0.2T	Silver Plating	

Part Number Table

Description	Part Number		
Jack, DC Power, PCB, R/A, 3 Way	2MJ-0401A110		

www.element14.com www.farnell.com www.newark.com

E:	DRAWING TITLE:							
/14	Jack, DC Power, PCB, R/A, 3 Way							
E:	SIZE	SIZE DWG NO.			ELECTRONIC FILE			
/14	A4	1876290-01		0001		1.0		
E:	SCAL	E: NTS	U.O.M.: mm SHEET: 1 of		SHEET: 1 of 1	I		