

Honeywell Sensing and Control

Search

21 CX16
(Home : Products : Switches » MICRO SWITCH™ Hazardous Location Switches » CX)

contacts

- ▶ Customer Service
- ▶ Technical Support
- ▶ Global Sales & Service
- ▶ View Site Demo
- ▶ Site Comments?

meet dr. larry

VIDEO - Dr. Larry Goldstein explains our newest and best technologies.



▶ Meet Dr. Larry

my links

- ▶ Login to iCOM
- ▶ Login to Rep/AD Portal
- ▶ Login to Digital University

News Center

- ▶ HONEYWELL EXPANDS ITS LIMITLESS™ PLATFORM WITH THE LAUNCH OF ITS GLOBALLY AVAILABLE INDUSTRIAL WIRELESS RECEIVER
- ▶ HONEYWELL EXTENDS ITS TRUSTABILITY® PRESSURE SENSOR PRODUCT LINE WITH A SINGLE SIDE LIQUID MEDIA OPTION
- ▶ HONEYWELL ADDS NEW 100° AND 180° ARC CONFIGURATIONS TO ITS SMART POSITION SENSOR PORTFOLIO
- ▶ HONEYWELL INTRODUCES ITS HAWK™ RESOLVERS 1-INCH SERIES, FULLY HOUSED CONFIGURATION
- ▶ HONEYWELL INTRODUCES MICROPOWER OMNIPOLAR DIGITAL HALL-EFFECT SENSOR ICS WITH LOW SUPPLY VOLTAGE AND ULTRA LOW TYPICAL CURRENT



narrow your search

- Products**
- Controls Monitoring and Lighting (286)
 - Machine Safety (1727)
 - Sensors (6004)
 - Switches (9781)
 - Wireless (45)
- Technology**
- Control and Instrumentation (988)
 - Electromechanical (9307)
 - Magnetic (541)
 - Platinum thin film (56)
 - Thick Film (1409)
 - More...



Explosion-Proof Limit Switches Series CX: Standard Housing: Side Rotary, Lever not included

Lever NOT Included
Actual product appearance may vary.
click here to download Hi-Res image

Sales & Service

Distributor Inventory

- Overview
- Specs
- Documentation
- Application Notes

Product Specifications

Availability	Global
Operating Force (OF)	0.50 Nm [.369 lb ft] max.
Pretravel (PT)	15° max.
Overtravel (OT)	90° min.
Differential Travel (DT)	10° max.
Product Type	MICRO SWITCH™ Weather-Sealed, Explosion-Proof Limit Switches
Actuator	Side Rotary
Lever Type	Lever Not Included - Reference Lever Required Accessory
Circuitry	1NC 1NO SPDT Snap Action; Maintained; 4 Basic Switches
Ampere Rating	15 A Ind/ 0.5 A Res./0.25 A Res.
Supply Voltage	120 Vac, 240 Vac or 480 Vac/125 Vdc/250 Vdc
Housing Material	Aluminum
Termination Type	0.75 in - 14NPT Conduit
Housing Type	CX: Standard: 145 mm [5.71 in]
Series Name	CX
Sealing	NEMA 1, 3, 4, 4x, 6, 6P, 7 (Class I, Division 1, Groups C, D), 9 (Class II, Division 1, Groups E, F, G), 13
CSA File #	LR57324
UL File #	E14274
Operating Temperature	-25 °C to 85 °C [-13 °F to 185 °F]
Comment	Maintained with continual CW and/or CCW rotation
Agency Approvals and Standards	UL, CSA
UNSPSC Code	302119
UNSPSC Commodity	302119 Switches and controls and relays
Sealed	Explosion-proof

new products

New Wireless Products

Go farther. Work smarter. Explore new possibilities. Just by cutting the cord and making the switch.



Wireless Web Site WGLA and WPMM XYR6000™

find out more

white papers

- ▶ Wireless Switches Offer Unlimited Benefit
- ▶ Basic Switches Are Not Created Equal
- ▶ Applying Precision Switches
- ▶ Sensors for Medical Devices
- ▶ New Ways to Measure Torque
- ▶ Choosing Safety Switches
- ▶ Specifying Hour Meters

Need help?

Click here to contact us