

PSD-S OE LED FL BU

Order No.: 2700134



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2700134>

LED flashing beacon element, 24 V DC, double lightning, blue

Commercial data

GTIN (EAN)	 4 046356 491266
Note	Made-to-order
sales group	K461
Pack	1 pcs.
Customs tariff	85318095
Catalog page information	Page 301 (NTK-2010)

Product notes

WEEE/RoHS-compliant since:
02/02/2009



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

General data

Diameter	70 mm
Height	65.5 mm
Material	Polycarbonate PC
Calotte color	blue
Weight	72 g

Ambient temperature (operation)	-20 °C ... 50 °C
Degree of protection	IP65, when installed or with cover
Mounting position	Any
Assembly instructions	Rubber seal pre-installed for each element

Electrical data

Input voltage	24 V DC
Maximum inrush current	max. 200 mA
Current consumption	35 mA
Service life, electrical	max. 50,000 h
Operating time	100 %
Optical signal type	LED flashing beacon with double flash
Signal frequency	Approx. 1 Hz

Approvals / conformities

Electromagnetic compatibility	Conformance with EMC Directive 2004/108/EC
-------------------------------	--

Certificates / Approvals



Certification

CUL Listed, UL Listed

Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2011 Phoenix Contact
Technical modifications reserved;