

# PSD-S OE LED RFL BU


Order No.: 2700135



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2700135>

LED random flashing beacon element, 24 V DC, blue

## Commercial data

GTIN (EAN)	 4 046356 491273
Note	Made-to-order
sales group	K461
Pack	1 pcs.
Customs tariff	85318095
Catalog page information	Page 301 (NTK-2010)

## Product notes

WEEE/RoHS-compliant since:  
02/02/2009



<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

## Technical data

### General data

Diameter	70 mm
Height	65.5 mm
Material	Polycarbonate PC
Calotte color	blue
Weight	78 g

Ambient temperature (operation)	-20 °C ... 50 °C
Degree of protection	IP65, when installed or with cover
Mounting position	Any
Assembly instructions	Rubber seal pre-installed for each element

#### Electrical data


Input voltage	24 V DC
Maximum inrush current	max. 500 mA
Current consumption	250 mA
Service life, electrical	max. 50,000 h
Operating time	100 %
Optical signal type	LED random flashing beacon (RLF)

#### Approvals / conformities

Electromagnetic compatibility	Conformance with EMC Directive 2004/108/EC
-------------------------------	--

#### Diagrams/Drawings

Dimensioned drawing



**Address**

PHOENIX CONTACT Inc., USA  
586 Fulling Mill Road  
Middletown, PA 17057, USA  
Phone (800) 888-7388  
Fax (717) 944-1625  
<http://www.phoenixcon.com>



© 2011 Phoenix Contact  
Technical modifications reserved;