

FLKM 50-PA-MELSEC A1S/32-0


Order No.: 2290342

The illustration shows version FLKM 50-PA-MELSEC A1S/32-I




<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2290342>

VARIOFACE front adapter, for Mitsubishi Electric MELSEC A1S Y81

Commercial data	
GTIN (EAN)	
Note	Made-to-order
sales group	I606
Pack	5 pcs.
Customs tariff	85369010
Catalog page information	Page 153 (IF-2002)

Product notes

WEEE/RoHS-compliant since:
02/28/2007



<http://www.download.phoenixcontact.com>
 Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

General	
Nominal voltage U_N	24 V AC/DC
Connection type, plug connector	Flat-ribbon cable plug connector in acc. with IEC 60603-13
Number of plug connectors	1
No. of positions, plug connector	50
Number of positions	50
Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C
Mounting position	Any
Standards/regulations	IEC 60664 IEC 60664 A DIN VDE 0110 DIN VDE 0160 (in parts)
Max. permissible current	1 A (per path) 8 A (per connection, supply via separate power supply)
Pollution degree	2
Surge voltage category	II

Supported controller	MITSUBISHI MELSEC A1S
Supported I/O card	Y81

Certificates / Approvals



Certification

GOST

Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2011 Phoenix Contact
Technical modifications reserved;