


PSD-S OE CL

Order No.: 2700099




<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2700099>

Permanent light element, 12 to 240 V AC/DC, clear, without bulb

| Commercial data | |
|--------------------------|--|
| GTIN (EAN) |  4 046356 491013 |
| sales group | K460 |
| Pack | 1 pcs. |
| Customs tariff | 85318095 |
| Catalog page information | Page 301 (NTK-2010) |

Product notes

WEEE/RoHS-compliant since:
02/02/2009



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

| Technical data | |
|---------------------|------------------|
| General data | |
| Diameter | 70 mm |
| Height | 65.5 mm |
| Material | Polycarbonate PC |
| Calotte color | clear |
| Weight | 55 g |

| | |
|---------------------------------|--|
| Ambient temperature (operation) | -20 °C ... 60 °C |
| Degree of protection | IP65, when installed or with cover |
| Mounting position | Any |
| Assembly instructions | Rubber seal pre-installed for each element |
| Base | B15d (bayonet) |

Electrical data

| | |
|-----------------------------|----------------------------|
| Nominal input voltage range | 12 V AC/DC ... 240 V AC/DC |
| Maximum inrush current | 21 mA () |
| Current consumption | 21 mA () |
| Source of light, power | 7 W |
| Service life, electrical | Depends on lamps |
| Operating time | 100 % |
| Optical signal type | Permanent light |

Approvals / conformities

| | |
|-------------------------------|---|
| Electromagnetic compatibility | Conformance with EMC directive 2004/108/EC and for low-voltage directive 2006/95/EC |
|-------------------------------|---|

Certificates / Approvals



Certification

CUL Listed, UL Listed

Accessories

| Item | Designation | Description |
|----------------|------------------|-----------------------------|
| General | | |
| 2700142 | PSD-S AS BULB 5W | Bulb, 5 W, 24 V, BA15d base |

Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2011 Phoenix Contact
Technical modifications reserved;