

Front adapters - FLKM S135/S400/SO124 - 2301765

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



The FLKM S135/S400/SO adapter links a SIMATIC® S5 plug directly with the basic SIMATIC® S7 400 card.
Conversion: S5 card 6ES5 456-4UA12 to S7 card 6ES7-422-1FH00-0AA0



Key Commercial Data

Packing unit	1 pc
Weight per Piece (excluding packing)	338.5 g
Custom tariff number	85369010
Country of origin	Germany

Technical data

Ambient conditions

Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C

General

Nominal voltage U _N	230 V AC
Max. permissible current	4 A (per path)
	4 A (per connection, supply via separate power supply)
Mounting position	vertical
Standards/regulations	DIN EN 50178
	IEC 62103

Connection data 1

Connection name	Field level
Connection method	SIEMENS S5-135 U pin strip

Supported controller

Controller	SIEMENS S5-135 U
------------	------------------

Front adapters - FLKM S135/S400/SO124 - 2301765

Technical data

Supported controller

- suitable I/O card	6ES5 456-4UA12
Controller	SIEMENS S7-400
- suitable I/O card	6ES7 422-1FH00-0AA0

Standards and Regulations

Standards/regulations	DIN EN 50178
	IEC 62103

Classifications

eCl@ss

eCl@ss 4.0	27250313
eCl@ss 4.1	27250313
eCl@ss 5.0	27250313
eCl@ss 5.1	27250313
eCl@ss 6.0	27249205
eCl@ss 7.0	27249205
eCl@ss 8.0	27249205
eCl@ss 9.0	27242220

ETIM

ETIM 2.0	EC000237
ETIM 3.0	EC000237
ETIM 4.0	EC000237
ETIM 5.0	EC002584


UNSPSC

UNSPSC 6.01	30211824
UNSPSC 7.0901	39121421
UNSPSC 11	39121421
UNSPSC 12.01	39121421
UNSPSC 13.2	39121421

Drawings

Front adapters - FLKM S135/S400/SO124 - 2301765

Circuit diagram



Connection scheme: FLKM S135/S400/SO124

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Phoenix Contact:](#)

[2301765](#)