

MINI-BAT/24DC/1.3AH

Order No.: 2866417

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2866417>

Rechargeable battery module, 24 V DC, 1.3 Ah, for use with MINI-UPS/2A and TRIO-UPS/5A

Commercial data

EAN	4046356152112
sales group	H061
Pack	1 pcs.
Customs tariff	85072098
Weight/Piece	2.1245 KG
Catalog page information	Page 592 (IF-2009)

<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data**Input data**

Nominal input voltage	24 V DC
-----------------------	---------

Output data

Nominal output voltage	24 V DC
Output current	max. 15 A
Connection in series	No
Output fuse	15 A

General data

Width	52 mm
-------	-------

Height	130 mm
Depth	110 mm
Weight	1.7 kg
Degree of protection	IP20
Class of protection	III
Ambient temperature (operation)	0 °C ... 40 °C
Ambient temperature (storage/transport)	0 °C ... 40 °C

Accessories

Item	Designation	Description
Fuse		
0913676	SI FORM C 15 A DIN 72581	Fuse modular terminal block, Nominal current: 15 A, Length: 19 mm, Width: 5 mm, Height: 13 mm, Color: light blue

Diagrams/Drawings

Block diagram



Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2010 Phoenix Contact
Technical modifications reserved;