



1. UNIT ACCEPTS 1.14 [.045] SQUARE OR ROUND POST.
  2. UNIT ACCEPTS STANDARD SL-156 CONTACTS.
  3. UNIT ACCEPTS KEYING PLUG 640254-1 AND KEYING PIN 640255-1.
  4. CIRCUIT ID. NUMBER(S) TO BE LOCATED SEQUENTIALLY AS SHOWN OR ONLY NO.1 CIRCUIT PLACED ON LOCKING RAMP.
  5. DIMENSIONS IN BRACKETS ARE IN INCHES.
- OPTIONAL CONSTRUCTION (BOTH CORNERS) UP TO 0.38 [.015] FOR P/N -1 THRU -5, UP TO 1.27 [.050] FOR P/N -6 THRU 2--4.

95.15	[3.746]	24	2-640250-4
91.19	[3.590]	23	2-640250-3
87.20	[3.433]	22	2-640250-2
83.24	[3.277]	21	2-640250-1
79.27	[3.121]	20	2-640250-0
75.31	[2.965]	19	1-640250-9
71.32	[2.808]	18	1-640250-8
67.36	[2.652]	17	1-640250-7
63.40	[2.496]	16	1-640250-6
59.44	[2.340]	15	1-640250-5
55.45	[2.183]	14	1-640250-4
51.49	[2.027]	13	1-640250-3
47.52	[1.871]	12	1-640250-2
43.56	[1.715]	11	1-640250-1
39.57	[1.558]	10	1-640250-0
35.61	[1.402]	9	640250-9
31.65	[1.246]	8	640250-8
27.69	[1.090]	7	640250-7
23.70	[.933]	6	640250-6
19.74	[.777]	5	640250-5
15.77	[.621]	4	640250-4
11.81	[.465]	3	640250-3
7.82	[.308]	2	640250-2
3.86	[.152]	1	640250-1
A ±0.25 [.010]		NO. OF CIRCUITS	

THIS DRAWING IS A CONTROLLED DOCUMENT.

INCHES	MM (INCHES)	UNLESS SPECIFIED	UNLESS SPECIFIED
FRONT VIEW	FRONT VIEW	FRONT VIEW	FRONT VIEW
TOP VIEW	TOP VIEW	TOP VIEW	TOP VIEW
RIGHT SIDE VIEW	RIGHT SIDE VIEW	RIGHT SIDE VIEW	RIGHT SIDE VIEW
LEFT SIDE VIEW	LEFT SIDE VIEW	LEFT SIDE VIEW	LEFT SIDE VIEW
REAR VIEW	REAR VIEW	REAR VIEW	REAR VIEW
ISOMETRIC VIEW	ISOMETRIC VIEW	ISOMETRIC VIEW	ISOMETRIC VIEW

TE Connectivity  
 HOUSING WITH LOCKING RAMP, SL-156

DATE: 10/07/79  
 DRAWING NO: 640250  
 CUSTOMER DRAWING