LOC	DIST
AD	00

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A1	REVISED PER ECO-11-004820	11MAR11	RK	HMR





RECOMMENDED HOLE LAYOUT

1. ASSEMBLY MAY BE BROKEN TO THE DESIRED NUMBER OF POSITIONS
2. TRUE POSITION TOLERANCE OF THE POST TIPS APPLIES WHEN THE HEADER IS HELD FLAT AGAINST THE PRINTED CIRCUIT BOARD

△3 THE NOTED DIMENSIONS APPLY AT THE INTERSECTION OF THE POST AND HOUSING

△4 HOUSING: FLAME RETARDANT THERMOPLASTIC; COLOR: BLACK.

△5 FINISH: 0.000381 [.000015] GOLD ON CONTACT AREA, 0.00254-0.00508 [.000100-.000200] MATTE TIN-LEAD ON SOLDER TAIL, ALL OVER 0.00127 [.000050] NICKEL.

△6 FINISH: 0.000381 [.000015] GOLD ON CONTACT AREA, 0.00254-0.00508 [.000100-.000200] MATTE TIN ON SOLDER TAIL, ALL OVER 0.00127 [.000050] NICKEL.

PLATING	G	F	E	NO. OF POSITIONS	PART NUMBER
△6	101.19 [3.984]	99.06 [3.900]	39	40	9-146475-0
△6	98.65 [3.884]	96.52 [3.800]	38	39	8-146475-9
△6	96.11 [3.784]	93.98 [3.700]	37	38	8-146475-8
△6	93.57 [3.684]	91.44 [3.600]	36	37	8-146475-7
△6	91.03 [3.584]	88.90 [3.500]	35	36	8-146475-6
△6	88.49 [3.484]	86.36 [3.400]	34	35	8-146475-5
△6	85.95 [3.384]	83.82 [3.300]	33	34	8-146475-4
△6	83.41 [3.284]	81.28 [3.200]	32	33	8-146475-3
△6	80.87 [3.184]	78.74 [3.100]	31	32	8-146475-2
△6	78.33 [3.084]	76.20 [3.000]	30	31	8-146475-1
△6	75.79 [2.984]	73.66 [2.900]	29	30	8-146475-0
△6	73.25 [2.884]	71.12 [2.800]	28	29	7-146475-9
△6	70.71 [2.784]	68.58 [2.700]	27	28	7-146475-8
△6	68.17 [2.684]	66.04 [2.600]	26	27	7-146475-7
△6	65.63 [2.584]	63.50 [2.500]	25	26	7-146475-6
△6	63.09 [2.484]	60.96 [2.400]	24	25	7-146475-5
△6	60.55 [2.384]	58.42 [2.300]	23	24	7-146475-4
△6	58.01 [2.284]	55.88 [2.200]	22	23	7-146475-3
△6	55.47 [2.184]	53.34 [2.100]	21	22	7-146475-2
△6	52.93 [2.084]	50.80 [2.000]	20	21	7-146475-1
△6	50.39 [1.984]	48.26 [1.900]	19	20	7-146475-0
△6	47.85 [1.884]	45.72 [1.800]	18	19	6-146475-9
△6	45.31 [1.784]	43.18 [1.700]	17	18	6-146475-8
△6	42.77 [1.684]	40.64 [1.600]	16	17	6-146475-7
△6	40.23 [1.584]	38.10 [1.500]	15	16	6-146475-6
△6	37.69 [1.484]	35.56 [1.400]	14	15	6-146475-5
△6	35.15 [1.384]	33.02 [1.300]	13	14	6-146475-4
△6	32.61 [1.284]	30.48 [1.200]	12	13	6-146475-3
△6	30.07 [1.184]	27.94 [1.100]	11	12	6-146475-2
△6	27.53 [1.084]	25.40 [1.000]	10	11	6-146475-1
△6	24.99 [.984]	22.86 [.900]	9	10	6-146475-0
△6	22.45 [.884]	20.32 [.800]	8	9	5-146475-9
△6	19.91 [.784]	17.78 [.700]	7	8	5-146475-8
△6	17.37 [.684]	15.24 [.600]	6	7	5-146475-7
△6	14.83 [.584]	12.70 [.500]	5	6	5-146475-6
△6	12.29 [.484]	10.16 [.400]	4	5	5-146475-5
△6	9.75 [.384]	7.62 [.300]	3	4	5-146475-4
△6	7.21 [.284]	5.08 [.200]	2	3	5-146475-3
△6	4.67 [.184]	2.54 [.100]	1	2	5-146475-2
△6	2.13 [.084]	-	-	1	5-146475-1

PLATING	G	F	E	NO. OF POSITIONS	PART NUMBER
△5	101.19 [3.984]	99.06 [3.900]	39	40	4-146475-0
△5	98.65 [3.884]	96.52 [3.800]	38	39	3-146475-9
△5	96.11 [3.784]	93.98 [3.700]	37	38	3-146475-8
△5	93.57 [3.684]	91.44 [3.600]	36	37	3-146475-7
△5	91.03 [3.584]	88.90 [3.500]	35	36	3-146475-6
△5	88.49 [3.484]	86.36 [3.400]	34	35	3-146475-5
△5	85.95 [3.384]	83.82 [3.300]	33	34	3-146475-4
△5	83.41 [3.284]	81.28 [3.200]	32	33	3-146475-3
△5	80.87 [3.184]	78.74 [3.100]	31	32	3-146475-2
△5	78.33 [3.084]	76.20 [3.000]	30	31	3-146475-1
△5	75.79 [2.984]	73.66 [2.900]	29	30	3-146475-0
△5	73.25 [2.884]	71.12 [2.800]	28	29	2-146475-9
△5	70.71 [2.784]	68.58 [2.700]	27	28	2-146475-8
△5	68.17 [2.684]	66.04 [2.600]	26	27	2-146475-7
△5	65.63 [2.584]	63.50 [2.500]	25	26	2-146475-6
△5	63.09 [2.484]	60.96 [2.400]	24	25	2-146475-5
△5	60.55 [2.384]	58.42 [2.300]	23	24	2-146475-4
△5	58.01 [2.284]	55.88 [2.200]	22	23	2-146475-3
△5	55.47 [2.184]	53.34 [2.100]	21	22	2-146475-2
△5	52.93 [2.084]	50.80 [2.000]	20	21	2-146475-1
△5	50.39 [1.984]	48.26 [1.900]	19	20	2-146475-0
△5	47.85 [1.884]	45.72 [1.800]	18	19	1-146475-9
△5	45.31 [1.784]	43.18 [1.700]	17	18	1-146475-8
△5	42.77 [1.684]	40.64 [1.600]	16	17	1-146475-7
△5	40.23 [1.584]	38.10 [1.500]	15	16	1-146475-6
△5	37.69 [1.484]	35.56 [1.400]	14	15	1-146475-5
△5	35.15 [1.384]	33.02 [1.300]	13	14	1-146475-4
△5	32.61 [1.284]	30.48 [1.200]	12	13	1-146475-3
△5	30.07 [1.184]	27.94 [1.100]	11	12	1-146475-2
△5	27.53 [1.084]	25.40 [1.000]	10	11	1-146475-1
△5	24.99 [.984]	22.86 [.900]	9	10	1-146475-0
△5	22.45 [.884]	20.32 [.800]	8	9	146475-9
△5	19.91 [.784]	17.78 [.700]	7	8	146475-8
△5	17.37 [.684]	15.24 [.600]	6	7	146475-7
△5	14.83 [.584]	12.70 [.500]	5	6	146475-6
△5	12.29 [.484]	10.16 [.400]	4	5	146475-5
△5	9.75 [.384]	7.62 [.300]	3	4	146475-4
△5	7.21 [.284]	5.08 [.200]	2	3	146475-3
△5	4.67 [.184]	2.54 [.100]	1	2	146475-2
△5	2.13 [.084]	-	-	1	146475-1

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: mm [INCHES]

TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ± -
1 PLC ± -
2 PLC ± 0.51[.02]
3 PLC ± 0.127[.005]
4 PLC ± 0.0127[.0005]
ANGLES ± -

MATERIAL △4

FINISH SEE TABLE

DWN	E. BRANDBERG	14MAR97
CHK	G. DUBNICZKI	14MAR97
APVD	G. DUBNICZKI	14MAR97
PRODUCT SPEC	—	
APPLICATION SPEC	—	
WEIGHT	—	

TE Connectivity

NAME: HEADER ASSEMBLY, MOD II, STACKING, SINGLE ROW, .025 SQ.POST, UNSHROUDED

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A1	00779	C-146475	—

CUSTOMER DRAWING | SCALE 4:1 | SHEET 1 OF 1 | REV A1

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

TE Connectivity:

2-146475-8