




BOARD-TO-BOARD HEADERS & RECEPTACLES



✓ Active

↓ **PRODUCT DRAWING**
English

↓ **3D PDF**

TE CONNECTIVITY (TE)

2X 4P HV100 REC CON. TE, 7.0MM, TIN

[AMPMODU](#) | [AMPMODU](#)

215308-4

TE Internal Number: 215308-4

Always EU RoHS/ELV Compliant

Connector Style **Receptacle**

Centerline **2.54 mm [.1 in]**

Number of Positions **4**

Packaging Method **Carton**

Contact Mating Area Plating Material **Tin**

Product Drawings

[HV 100 VERTICAL CONNECTOR DUAL ROW, 7,0mm HEIGHT, TOP ENTRY, TIN](#)

PDF
English

CAD Files

[3D PDF](#)

PDF
3D

[Customer View Model](#)

2D_DXF.ZIP
English

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Connector Style

Receptacle

PCB Mounting Orientation

Vertical

Row-to-Row Spacing (mm)

2.54

Profile

Standard

Applies To

Printed Circuit Board

Product Type

Connector

Boss

Without

Series

AMPMODU, HV-100

	Sealed	No
	Connector Type	Connector Assembly
Configuration Features	Number of Positions	4
	Number of Rows	2
	Stackable	Yes
Contact Features	Contact Mating Area Plating Material	Tin
	Contact Shape	Square
	Contact Current Rating (A)	3
	Contact Type	Socket
	Solder Tail Contact Plating Material	Tin-Lead over Nickel
	Solder Tail Contact Plating Thickness (µm)	2.4 – 4
	Contact Base Material	Phosphor Bronze
Termination Features	Termination Method to PC Board	Through Hole - Solder
	Termination Post Length	3.1 mm [.122 in]
Mechanical Attachment	Mating Alignment Type	Polarization
	PCB Mount Retention	With
	PCB Mount Retention Type	Retention Solder Tails
Housing Features	Centerline	2.54 mm [.1 in]
	Housing Material	Polyester - GF
	Housing Color	Black
	Housing Entry Style	Closed Bottom, Closed Entry, Top
Dimensions	Height	7 mm [.276 in]
	PCB Thickness (Recommended) (mm)	1.6
Usage Conditions	Operating Temperature Range (°C)	-55 – 105
Operation/Application	Pick and Place Cover	Without
	Assembly Process Feature	Board Standoff
	For Use With	Header Assembly

Industry Standards	UL Flammability Rating	UL 94V-0
	MIL-C-55032	No
Packaging Features	Packaging Method	Carton
	Packaging Quantity	184
Product Compliance	Statement of Compliance PDF	
	VIEW ALL PRODUCT COMPLIANCE	