

Inline connector - IB IL SCN-8-AC-REL - 2740290

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Plug, for digital 1, 2 or 8-channel Inline terminals with AC voltage



Key commercial data

Packing unit	1 pc
Minimum order quantity	10 pc
Weight per Piece (excluding packing)	15.09 GRM
Custom tariff number	85366990
Country of origin	Germany

Technical data

Dimensions

Height	111.2 mm
Depth	41 mm
Width	12 mm

Classifications

eCl@ss

eCl@ss 4.0	27250281
eCl@ss 4.1	27250281
eCl@ss 5.0	27259205
eCl@ss 5.1	27242692
eCl@ss 6.0	27242692
eCl@ss 7.0	27242692
eCl@ss 8.0	27242692

ETIM

ETIM 2.0	EC000313
----------	----------

Inline connector - IB IL SCN-8-AC-REL - 2740290

Classifications

ETIM

ETIM 3.0	EC000313
ETIM 4.0	EC002584
ETIM 5.0	EC002584

UNSPSC

UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404
UNSPSC 11	39121311
UNSPSC 12.01	39121311
UNSPSC 13.2	39121311

Approvals

Approvals

Approvals

UL Recognized / cUL Recognized / GOST / cULus Recognized

Ex Approvals

Approvals submitted

Approval details

UL Recognized 	
mm²/AWG/kcmil	26-14
Nominal current I _N	10 A
Nominal voltage U _N	120 V

Inline connector - IB IL SCN-8-AC-REL - 2740290

Approvals

cUL Recognized 	
mm²/AWG/kcmil	26-14
Nominal current I _N	10 A
Nominal voltage U _N	120 V

GOST 
--

cULus Recognized 
--