

Temperature measuring transducer - MACX MCR-EX-SL-TC-I-NC - 2865586

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Ex-i temperature measuring transducer: Converts signals from thermocouples installed in Ex areas and mV sources and transmits a 0/4-20 mA signal to a load in a safe area. Freely programmable, 3-way isolation

Why buy this product

- Input for resistance thermometers and resistance-type sensors, [Ex ia] IIC
- Power supply possible via DIN rail connector
- Programming during operation with Ex measuring circuit connected and also voltage-free using IFS-USB-PROG-ADAPTER programming adapter
- Installation in zone 2, protection type "n" (EN 60079-15) permitted
- 3-way electrical isolation
- Status indicator for supply voltage, cable, sensor, and module errors
- 0 ... 20 mA or 4 ... 20 mA output
- Configuration via software (FDT/DTM): sensor type, connection technology, measuring range, measuring unit, filter, alarm signal, and output range



Key Commercial Data

Packing unit	1 pc
GTIN	 4 046356 160513
Weight per Piece (excluding packing)	152.7 g
Custom tariff number	85437090
Country of origin	Germany
Note	Made to Order (non-returnable)

Technical data

Note

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---

Temperature measuring transducer - MACX MCR-EX-SL-TC-I-NC - 2865586

Technical data

Dimensions

Width	12.5 mm
Height	99 mm
Depth	114.5 mm

Ambient conditions

Ambient temperature (operation)	-20 °C ... 60 °C (Any mounting position)
Ambient temperature (storage/transport)	-40 °C ... 80 °C
Maximum altitude	≤ 2000 m
Permissible humidity (operation)	5 % ... 95 % (non-condensing)
Noise immunity	EN 61000-6-2 When being exposed to interference, there may be minimal deviations.
Degree of protection	IP20

Input data

Input	Intrinsically safe
Sensor types that can be used (TC)	E, J, K, N as per IEC / EN 60584, L as per DIN 43760
Temperature measuring range	-250 °C ... 1372 °C (Range depending on the sensor type)
Input signal range	-20 mV ... 70 mV
Measuring range span	Min. 50 K for thermocouples, 3 mV for mV sources

Output data

Signal output	Current output
Current output signal	0 mA ... 20 mA
	4 mA ... 20 mA
Load/output load current output	≤ 500 Ω
Output ripple (current)	< 50 μA _{pp}
Behavior in the event of a sensor error	As per NE 43 or can be freely defined

Power supply

Nominal supply voltage	24 V DC
Supply voltage range	19.2 V DC ... 30 V DC (24 V DC (-20% ... +25%))
Max. current consumption	< 40 mA (24 V DC)
Power consumption	< 1 W

Connection data

Conductor cross section solid min.	0.2 mm ²
Conductor cross section solid max.	2.5 mm ²
Conductor cross section flexible min.	0.2 mm ²
Conductor cross section flexible max.	2.5 mm ²
Conductor cross section AWG min.	24
Conductor cross section AWG max.	14
Stripping length	7 mm

Temperature measuring transducer - MACX MCR-EX-SL-TC-I-NC - 2865586

Technical data

Connection data

Screw thread	M3
Connection method	Screw connection
Tightening torque, min	0.5 Nm
Tightening torque max	0.6 Nm

General

No. of channels	1
Temperature coefficient, typical	0.01 %/K
Typical cold point errors	± 1 K
Step response (0–99%)	typ. 700 ms
	≤ 1100 ms
Alignment zero	± 5 %
Alignment span	± 5 %
Status display	Green LED (supply voltage, PWR)
	Red LED, flashing (line, sensor error, ERR)
	Red LED (module error, ERR)
Inflammability class according to UL 94	V0
Pollution degree	2
Surge voltage category	II
Emitted interference	EN 61000-6-4
Housing material	PA 66-FR
Color	green
Designation	Input/output/power supply
Electrical isolation	300 V _{rms} (Rated insulation voltage (surge voltage category II; pollution degree 2, safe isolation as per EN 61010-1))
	2.5 kV (50 Hz, 1 min., test voltage)
Designation	Input/output
Electrical isolation	375 V (Peak value in accordance with EN 60079-11)
Designation	Input/power supply
Electrical isolation	375 V (Peak value in accordance with EN 60079-11)
Conformance	CE-compliant, additionally EN 61326
ATEX	# II (1) G [Ex ia Ga] IIC/IIB
	# II (1) D [Ex ia Da] IIIC
	# II 3(1) G Ex nA ic [ia Ga] IIC T4 Gc X
IECEX	[Ex ia Ga] IIC/IIB
	[Ex ia Da] IIIC
	Ex nA ic [ia Ga] IIC T4 Gc
UL, USA / Canada	Class I Div 2; IS for Class I, II, III Div 1

Safety characteristic data

Integrity requirement	IEC 61508 - Low demand
-----------------------	------------------------

Temperature measuring transducer - MACX MCR-EX-SL-TC-I-NC - 2865586

Technical data

Safety characteristic data

Architecture	Single-channel, 1oo1
Equipment type	Type B
Safety Integrity Level (SIL)	2
Safe Failure Fraction (SFF)	96.5 %
MTBF	123 Years
λ_{SU}	1.42×10^{-7} (142 FIT)
λ_{SD}	4.38×10^{-7} (438 FIT)
λ_{DU}	3.24×10^{-8} (32.4 FIT)
λ_{DD}	3.14×10^{-7} (314 FIT)
Probability of a hazardous failure on demand (PFD _{AVG})	1.31 x 10 ⁻⁴ (1 year)
	2.62 x 10 ⁻⁴ (2 years)
	3.93 x 10 ⁻⁴ (3 years)
	6.55 x 10 ⁻⁴ (5 years)
	9.17 x 10 ⁻⁴ (7 years)
	1.05 x 10 ⁻³ (8 years)
Diagnostic coverage (DC)	90.7 %
Integrity requirement	IEC 61508 - High demand
Architecture	Single-channel, 1oo1
Equipment type	Type B
Safety Integrity Level (SIL)	Up to 2
Safe Failure Fraction (SFF)	90.7 %
MTBF	123 Years
λ_{SU}	1.42×10^{-7} (150 FIT)
λ_{SD}	4.38×10^{-7} (438 FIT)
λ_{DU}	3.24×10^{-8} (32.4 FIT)
λ_{DD}	3.14×10^{-7} (314 FIT)
Probability of a hazardous failure per hour (PFH _D)	3,24 x 10 ⁻⁸
Diagnostic coverage (DC)	90.7 %

Safety data

Max. output voltage U _o	6 V
Max. output current I _o	4.7 mA
Max. output power P _o	7 mW
Group	IIC
Max. external inductivity L _o	100 mH
Max. external capacity C _o	1.5 µF
Group	IIC

Temperature measuring transducer - MACX MCR-EX-SL-TC-I-NC - 2865586

Technical data

Safety data

Max. external inductivity L_o	10 mH
Max. external capacity C_o	1.9 μ F
Group	IIC
Max. external inductivity L_o	1 mH
Max. external capacity C_o	2.7 μ F
Group	IIB
Max. external inductivity L_o	100 mH
Max. external capacity C_o	7 μ F
Group	IIB
Max. external inductivity L_o	10 mH
Max. external capacity C_o	9.4 μ F
Group	IIB
Max. external inductivity L_o	1 mH
Max. external capacity C_o	15 μ F
Safety-related maximum voltage U_m	253 V AC (125 V DC)

EMC data

Designation	Electromagnetic RF field
Standards/regulations	EN 61000-4-3
Typical deviation from the measuring range final value	3 %
Designation	Fast transients (burst)
Standards/regulations	EN 61000-4-4
Typical deviation from the measuring range final value	3 %
Designation	Conducted interferences
Standards/regulations	EN 61000-4-6
Typical deviation from the measuring range final value	3 %

Classifications

eCl@ss

eCl@ss 4.0	27200206
eCl@ss 4.1	27200206
eCl@ss 5.0	27200206
eCl@ss 5.1	27200206
eCl@ss 6.0	27200206
eCl@ss 7.0	27200206
eCl@ss 8.0	27371503

Temperature measuring transducer - MACX MCR-EX-SL-TC-I-NC - 2865586

Classifications

ETIM

ETIM 2.0	EC001446
ETIM 3.0	EC001446
ETIM 4.0	EC001446
ETIM 5.0	EC002568

UNSPSC

UNSPSC 6.01	30211506
UNSPSC 7.0901	39121008
UNSPSC 11	39121008
UNSPSC 12.01	39121008
UNSPSC 13.2	39121008

Approvals

Approvals

Approvals

UL Listed / cUL Listed / Functional Safety / EAC / cULus Listed

Ex Approvals

IECEx / ATEX / UL Listed / cUL Listed / cULus Listed

Approvals submitted

Approval details

UL Listed

cUL Listed

Functional Safety

EAC

Temperature measuring transducer - MACX MCR-EX-SL-TC-I-NC - 2865586

Approvals



Accessories

Accessories

Programming adapter


Programming adapter - IFS-USB-PROG-ADAPTER - 2811271



Programming adapter with USB interface, for programming with software. The USB driver is included in the software solutions for the products to be programmed, such as measuring transducers or motor managers.

Drawings

Dimensional drawing



Block diagram

