

IB IL 24 PWR IN/2F-D-2MBD-PAC


Order No.: 2863821

The illustration shows the version IB IL 24 PWR INF-PAC



<http://catalog.phoenixcontact.net/phoenix/treeViewClick.do?UID=2863821>

Inline power terminal block, complete with accessories (connector and labeling field), 24 V DC, with fuse (main and segment voltage) and diagnostics, transmission speed 2 Mbaud

Commercial data	
EAN	 4 017918 977726
Note	Made-to-order
sales group	K417
Pack	1 Pcs.
Customs tariff	85389091
Gross weight in pieces	0.0838 KG
Net weight per piece	0.06949 KG
Catalog page information	Page 267 (AX-2009)

Product notes

WEEE/RoHS-compliant since:
07/04/2006



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data	
Dimensions	
Width	12.2 mm
Height	119.8 mm
Depth	71.5 mm
Interfaces	
Interface	Inline local bus

Inline potentials

Current consumption from U_L	max. 45 mA DC
Main circuit supply U_M	24 V DC (nominal value)
Supply voltage range U_M	19.2 V ... 30 V (including all tolerances, including ripple)
Power supply at U_M	4 A (nominal value)
Segment supply voltage U_S	24 V DC -15 % / +20 % (acc. to EN 61131-2)
Power supply at U_S	4 A (nominal value)

Certificates / Approvals

Certification

Certifications applied for:

Certification Ex:

Accessories

Item	Designation	Description
------	-------------	-------------

Connector/Adapter

2727462	IB IL SCN-PWR IN	Connector, for Inline power and segment terminal blocks
2727637	IB IL SCN-PWR IN-CP	Connector, colored, for Inline power and segment terminal blocks

Marking

0809492	ESL 62X10	Insert strip, Sheet, white, unlabeled, can be labeled with: Office printing systems, Plotter: Laser printer, Mounting type: Insert, Lettering field: 62 x 10 mm
2727501	IB IL FIELD 2	Labeling field, width: 12.2 mm

Address

PHOENIX CONTACT Deutschland GmbH
Flachmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>



© 2014 Phoenix Contact
Technical modifications reserved;