



RECTANGULAR POWER CONNECTORS



TE CONNECTIVITY (TE)

MICRO MNL HDR ASSY SINGLE ROW

MATE-N-LOK | Micro MATE-N-LOK

2-1445057-7

TE Internal Number: 2-1445057-7

Always EU RoHS/ELV Compliant

Product Type **Header**

Housing Type **Plug**

Connector System **Wire-to-Board**

Applies To **Printed Circuit Board**

Contact Current Rating (A) **5**

Active

PRODUCT DRAWING
English

3D PDF

Product Drawings

RT ANGLE SURFACE MOUNT HEADER ASSY, TIN CONTACTS W/SURF MOUNT
HOLDDOWNS,

PDF
English

CAD Files

Customer View Model

2D_DXF.ZIP
English

3D PDF

PDF
3D

Customer View Model

3D_IGS.ZIP
English

Customer View Model

3D_STP.ZIP
English

Catalog Pages/Data Sheets

SOFT_SHELL_PIN_AND_SOCKET_CONNECTORS_CATALOG

PDF
English

1773458-4_MICRO_MATE_N_LOK_CONNECTOR_SYSTEM_QRG

PDF
English

Product Specifications

Application Specification

Micro MATE-N-LOK Connectors

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Product Type	Header
	Housing Type	Plug
	Contact Type	Pin
Configuration Features	Number of Positions	7
	Centerline	3 mm [.118 in]
	PCB Mounting Orientation	Right Angle
	Number of Rows	1
	Multiple Contact Types	Without
	Contact Layout	Inline
Electrical Characteristics	Contact Current Rating (A)	5
	Operating Voltage (VAC)	250
	Operating Voltage (VDC)	250
Contact Features	Contact Retention	Without
	Contact Termination Area Plating Material	Tin
	Contact Termination Area Plating Thickness	2.54 μm [100 μin]
Termination Features	Wire/Cable Size (AWG)	30 – 20
	Termination Method to Wire/Cable	Solder
	Termination Method to PC Board	Surface Mount
	Termination Post/Tail Length	1.4 mm [.055 in]
Mechanical Attachment	Mating Alignment	With
	Mating Retention	With
	PCB Mount Retention	With
	PCB Mount Retention Type	Hold-Down Posts
	Mating Retention Type	Locking Tab
	Panel Mount Retention	Without
	Strain Relief	Without
	Mating Alignment Type	Polarization
Housing Features	UL Flammability Rating	UL 94V-0
	Housing Color	Black
	Housing Material	High Temperature Nylon
	Boardlock Material	Phosphor Bronze

Dimensions	Insulation Diameter (Max) (mm)	1.52
	PCB Thickness (Recommended)	1.57 mm [.062 in]
Usage Conditions	Sealed Condition	Not Sealed
Operation/Application	Connector System	Wire-to-Board
	Applies To	Printed Circuit Board
	Operating Temperature	-40 – 105 °C [-40 – 221 °F]
Industry Standards	UL Rating	Recognized
	CSA File Number	LR7189
	Agency/Standard	CSA, UL
	VDE Tested	Yes
	CSA Rating	Certified
	Agency/Standard Number	E28476
Packaging Features	Packaging Method	Tape
	Packaging Quantity	215
Other	For Use With	Receptacle Housing

Product Compliance [Statement of Compliance PDF](#)
[VIEW ALL PRODUCT COMPLIANCE](#)


CUSTOMERS ALSO BOUGHT

<p>SURFACE MOUNT RESISTORS</p> <p>CPF 0402 4K87 0.1% 25PPM 1K RL CPF0402B4K87E1</p> <p> Save to List Find Similar Products</p>	<p>BOARD-TO-BOARD HEADERS & RECEPTACLES</p> <p>12 MODIV VRT DR CE 100/125 534998-6</p> <p> Save to List Find Similar Products</p>	<p>SURFACE MOUNT RESISTORS</p> <p>RLP73M 3A R022 1% 1K RL RLP73M3AR022FTDF</p> <p> Save to List Find Similar Products</p>	<p>SURFACE MOUNT RESISTORS</p> <p>CPF 0402 8K45 0.1% 25PPM 1K RL CPF0402B8K45E1</p> <p> Save to List Find Similar Products</p>
---	--	--	---

Products - 1 Results

[View All](#)

[Compare 0/10](#) 

Relation Type 

RELATIONSHIP

Mating Products

Used to identify Mating Parts

[See All Mating Products](#)

PRODUCT - MATING PRODUCTS



Connectors - Rectangular Power Connectors
MATE-N-LOK | Micro MATE-N-LOK

Always EU RoHS/ELV Compliant

**MICRO MNL RFECEPT
HSG SINGLE R
- 1445022-7**

TE INTERNAL NUMBER: 1445022-7

 Active