

Power module - EMD-SL-PS45-500AC - 2885317

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Power modules, pluggable, for EMD-FL-..., supply voltage: 425...550 V AC

Why buy this product

- Monitoring range up to 7.2 kW
- Temperature monitoring of the motor winding
- Variable supply voltage range
- Separately adjustable startup and response delays
- Detection of switched off loads



Key Commercial Data

Packing unit	1 STK
GTIN	 4 017918 996550
GTIN	4017918996550
Weight per Piece (excluding packing)	94.200 g
Custom tariff number	85043180
Country of origin	Germany

Technical data

Dimensions

Width	32 mm
Height	35 mm
Depth	26 mm

Ambient conditions

Power module - EMD-SL-PS45-500AC - 2885317

Technical data

Ambient conditions

Ambient temperature (operation)	-25 °C ... 55 °C
Ambient temperature (storage/transport)	-25 °C ... 70 °C

Input data

Nominal input voltage	500 V AC (50/60 Hz)
-----------------------	---------------------

Classifications

eCl@ss

eCl@ss 5.0	27049002
eCl@ss 5.1	27049002
eCl@ss 6.0	27049002
eCl@ss 7.0	27049002
eCl@ss 8.0	27049002
eCl@ss 9.0	27040701

ETIM

ETIM 4.0	EC002540
ETIM 5.0	EC002540
ETIM 6.0	EC002540

UNSPSC

UNSPSC 6.01	30211916
UNSPSC 7.0901	39121535
UNSPSC 11	39121535
UNSPSC 12.01	39121535
UNSPSC 13.2	39121004

Approvals

Approvals

Approvals

EAC

Ex Approvals

Power module - EMD-SL-PS45-500AC - 2885317

Approvals

Approval details

EAC		RU C- DE.A*30.B.01082
-----	---	--------------------------